

E-BIKE 2024



Atala
WHISTLE

Atala WHISTLE

E-MTB FULL SUSPENDED

Pedalare fino alla cima e attaccare velocemente le discese più tecniche alla massima velocità. Sono costruite per le competizioni, ma grazie alla robuste sospensioni, sono agili e divertenti anche sui sentieri vicino a casa.

Ride to the top and quickly attack the most technical descents at maximum speed. Are built for competitions but thanks to the sturdy suspensions, they are agile and fun even on trails near home.



E-HARDTAIL

Percorsi sterrati, salite da affrontare con agilità, discese impegnative. Le nostre eMTB Hardtail sono perfette per affrontare ogni tipo di trail.

Dirt panths, agility climb, demanding descents. Our Hardtail eMtb are perfect for all types of trails.



E-GRAVEL

Scegliere i tuoi itinerari senza doverli pianificare, affrontando sia sentieri off-road sia lunghi tratti di asfalto, è possibile con una gravel eBike. Ideale per viaggi avventurosi e perfettamente performanti anche in città, la gravel è agile, affidabile e confortevole.

With a gravel is possible to choose your own routes without planning team, tackle both off-road trails and long stretches of asphalt. Ideal for adventures trips and perfectly performing even in the city, the gravel is agile, reliable and comfortable.



E-TREKKING

Stare a contatto con la natura, esplorare, scoprire, combinando il relax con l'esercizio fisico. Solamente la tua eBike rende ogni viaggio più piacevole.

Being surrounded by nature, discover, explore, combining relax with exercise. Your eBike makes every journey more pleasant.



E-URBAN

Spostarsi velocemente in città è sempre più difficile: strade intasate, metro affollatissime, treni in ritardo fanno ormai parte del passato. L'eBike ti permette questo e molto altro, diventando parte integrante della mobilità urbana.

Moving quickly in the city is more and more difficult: congested streets, stuffy subways, train delays. Not any more. The eBike makes commuting easier, becoming an essential part of urban mobility.



E-Full Suspended

B-Rush #MISSIONCARBON







I nostri nuovi telai B-Rush nascono da un progetto esclusivo per il marchio Whistle:

- * **Nuovo Design.** La progettazione delle forme e l'ingegnerizzazione degli stampi è realizzata appositamente dal nostro staff tecnico.
- * **Materiali all'avanguardia.** Resistenza, leggerezza e comfort sono garantiti dalla fibra di Carbonio T700, ottenuta attraverso processi ad altissima temperatura e scelta per le sue elevate prestazioni meccaniche associate ad un peso ridotto.
- * **Produzione Smart.** Prodotto attraverso le più moderne tecnologie nel campo dei materiali compositi, che permettono di ottimizzare i tempi di realizzazione di ogni telaio.
- * **Il risultato?** Un prodotto dalle prestazioni uniche, in grado di soddisfare gli utilizzatori più esigenti, al miglior prezzo di mercato.

Our new B-Rush frames are born from an exclusive project for the Whistle brand:

- * **New Design.** The design of the shapes and the engineering of the molds is carried out by our technical staff.
- * **State-of-the-art materials.** Resistance, lightness and comfort are guaranteed by the T700 carbon fiber, obtained through very high temperature processes and chosen for its high mechanical performance associated with low weight.
- * **Smart manufacturing.** Produced through the most modern technologies in the field of composite materials, which allows to realize the realization times of each frame.
- * **The result?** A product with unique performances, able to satisfy the most demanding users, at the best market price.









-  Bosch Perf. CX Race Smart System
-  PowerTube 750Wh
-  Kiox 300 + Led Remote
-  29"
-  12s
-  26,8 kg

Black/ Gold	
40	0116867400
44	0116867410
48	0116867420
52	0116867430

Frame	Full Carbon 29", Toray T700, Integrated battery, Internal routing, Rear travel 160 mm, 12x148 mm E-Thru
Fork	Fox 38 Float Factory eMTB+, 160mm, Air, 1.5 tapered, FIT4, 15x110 mm
Rear Shock	Fox Float X2 Performance Elite, EVOL, LSR, HSR, 2 Pos-Lever, 230x65
Headset	Acros for Ursa, 1,5", Internal routing
Crankset	FSA 36T MegaTooth
Rear Derailleur	Shimano XT RD-M8100 SGS, Shadow Plus
Shifters Levers	Shimano XT SL-M8100 Rapidfire-Plus, 12s
Brakes	Shimano XT BR-M8120, Four piston, Rotor RT-MT800 203mm/ 203mm
Cassette	Shimano CS-M8100 12s 10/51
Pedals	Alu MTB Full+
Wheels	Mavic E-Deemax 29", International, Microspline
Stem	Satori Ursa, 35 mm, Internal routing
Handlebar	Race Face Chester, 35 mm, 780mm, Rise 20
Seatpost	Dropper Alpha 1, 31,6 mm, remote
Saddle	Whistle Performance
Tyres	F: Michelin Wild Enduro Front, 29"x2.40" R: Michelin Wild Enduro Rear 29"x2.40"

Motor	Bosch Smart System Perf. CX Race, 36 V, 250 W
Max Torque	85 Nm
Sensor Type	Torque
Battery	PowerTube 750 Horizontal, frametype, weight 4,2 kg
Charger Type	4 A
Change Time	Up to 6 hours
Max Assisted Speed	25 km/h
Display	Kiox 300 + Led Remote
Power	Eco: 60 % Tour+: 60-340 % EMTB: 140-340 % Turbo: 400 %









-  Bosch Perf. CX Smart System
-  PowerTube 750Wh
-  Kiox 300 + Led Remote
-  29"
-  12s
-  27 kg

Black/ Gold	
40	0116862000
44	0116862010
48	0116862020
52	0116862030

Frame	Full Carbon 29", Toray T700, Integrated battery, Tapered, Internal routing, Rear travel 160 mm, 12x148 mm E-Thru
Fork	Fox 38 Float Factory eMTB+, Air, FIT4, 29", Travel 160 mm, 1,5 Tapered, 15x110 mm
Rear Shock	Fox Float X2 Factory, EVOL, LSR, HSR, 2 Pos-Lever, 230x65
Headset	Acros for Ursa, 1,5", Internal routing
Crankset	Miche Black Box, FSA 36T MegaTooth
Rear Derailleur	Shimano XT RD-M8100 SGS, Shadow Plus
Shifters Levers	Shimano XT SL-M8100 Rapidfire-Plus, 12s
Brakes	Shimano XT BR-M8120, Four piston, Rotor RT-MT800 203 mm / 203 mm
Cassette	Shimano CS-M8100 12s 10/51
Pedals	Alu MTB Full+
Wheels	Mavic E-Deemax 29"
Stem	Satori Ursa, Barbore 35 mm
Handlebar	Race Face Chester, 780 mm, Barbore 35, Rise 20
Seatpost	Race Face Transfer Factory Kashima, 31,6 mm, remote
Saddle	Whistle Performance
Tyres	Vittoria Mazza 29"x2,60"

Motor	Bosch Smart System Perf. CX 36 V, 250 W
Max Torque	85 Nm
Sensor Type	Torque
Battery	PowerTube 750 Horizontal, frametype, weight 4,2 kg
Charger Type	4 A
Change Time	Up to 6 hours
Max Assisted Speed	25 km/h
Display	Kiox 300 + Led Remote
Power	Eco: 60 % Tour+: 60-340 % EMTB: 140-340 % Turbo: 340 %









-  Bosch Perf. CX Smart System
-  PowerTube 750Wh
-  Kiox 300 + Led Remote
-  29"
-  12s
-  27,2 kg

Black/ Red	
40	0116862200
44	0116862210
48	0116862220
52	0116862230

Frame	Full Carbon 29", Toray T700, Integrated battery, Tapered, Internal routing, Rear travel 160 mm, 12x148 mm E-Thru
Fork	Fox 36 Float Performance eMTB+, Air, GRIP, 29", Travel 160mm, 1.5 Tapered, 15x110mm
Rear Shock	Fox Float X Performance, EVOL, LSR, 2 Pos-Lever, 230x65
Headset	Acros for Ursa, 1.5", Internal routing
Crankset	Miche Black Box, FSA 36T MegaTooth
Rear Derailleur	Shimano XT RD-M8100 SGS, Shadow Plus
Shifters Levers	Shimano SLX SL-M7100 Rapidfire-Plus, 12s
Brakes	Magura MT5, Four piston, Rotor RT30 203 mm / 203 mm
Cassette	Shimano CS-M6100 12s 10/51
Pedals	Alu MTB Full+
Wheels	Mavic E-Crossride 29"
Stem	Satori Ursa, Barbore 35 mm
Handlebar	Alu, 780 mm, 35mm, Rise 15mm
Seatpost	Dropper Alpha 1, 31.6 mm, remote
Saddle	Whistle Performance
Tyres	F: Schwalbe Magic Mary Evo, Addix Soft, Super Trail, 29"x2,60" R: Schwalbe Hans Dampf Evo, Addix Soft, Super Trail, 29"x2,60"

Motor	Bosch Smart System Perf. CX 36 V, 250 W
Max Torque	85 Nm
Sensor Type	Torque
Battery	PowerTube 750 Horizontal, frametype, weight 4,2 kg
Charger Type	4 A
Change Time	Up to 6 hours
Max Assisted Speed	25 km/h
Display	Kiox 300 + Led Remote
Power	Eco: 60 % Tour+: 60-340 % EMTB: 140-340 % Turbo: 340 %









-  Bosch Perf. CX Smart System
-  PowerTube 750Wh
-  Kiox 300 + Led Remote
-  29"
-  12s
-  27,2 kg

Black/ Gold	
40	0116863900
44	0116863910
48	0116863920
52	0116863930

Frame	Full Carbon 29", Toray T700, Integrated battery, Tapered, Internal routing, Rear travel 160 mm, 12x148 mm E-Thru
Fork	Fox 36 Float Performance eMTB+, 160 mm, Air, 1.5 Tapered, GRIP, 15x110 mm
Rear Shock	Fox Float X Performance, EVOL, LSR, 2 Pos-Lever, 230x65
Headset	Acros for Ursa, 1,5", Internal routing
Crankset	Miche Black Box, FSA 36T MegaTooth
Rear Derailleur	Shimano XT RD-M8100 SGS, Shadow Plus
Shifters Levers	Shimano SLX SL-M7100 Rapidfire-Plus, 12s
Brakes	Magura MT5, Four piston, Rotor RT30 203 mm / 203 mm
Cassette	Shimano CS-M6100 12s 10/51
Pedals	Alu MTB Full+
Wheels	Shimano WH-M620
Stem	Satori Ursa, 35 mm, Internal routing
Handlebar	Alu, 780 mm, 35mm, Rise 15mm
Seatpost	Dropper Alpha 1, 31,6 mm, remote
Saddle	Whistle Performance
Tyres	F: Schwalbe Magic Mary Evo, Addix Soft, Super Trail, 29"x2,60" R: Schwalbe Hans Dampf Evo, Addix Soft, Super Trail, 29"x2,60"

Motor	Bosch Smart System Perf. CX 36 V, 250 W
Max Torque	85 Nm
Sensor Type	Torque
Battery	PowerTube 750 Horizontal, frametype, weight 4,2 kg
Charger Type	4 A
Change Time	Up to 6 hours
Max Assisted Speed	25 km/h
Display	Kiox 300 + Led Remote
Power	Eco: 60 % Tour+: 60-340 % EMTB: 140-340 % Turbo: 340 %









-  Bosch Perf. CX Smart System
-  PowerTube 750Wh
-  Kiox 300 + Led Remote
-  29"
-  12s
-  27,4 kg

Black/ Green	
40	0116862305
44	0116862315
48	0116862325
52	0116862335

Frame	Full Carbon 29", Toray T700, Integrated battery, Tapered, Internal routing, Rear travel 160 mm, 12x148 mm E-Thru
Fork	Rock Shox Domain RC e-MTB, DebonAir, 29", Travel, 150 mm, 1.5 Tapered, Maxle Lite 15x110 mm
Rear Shock	Rock Shox Deluxe Select R, DebonAir, 230x65 mm
Headset	Acros for Ursa, 1.5", Internal routing
Crankset	Miche Black Box, FSA 34T MegaTooth
Rear Derailleur	Shimano XT RD-M8100 SGS, Shadow Plus
Shifters Levers	Shimano SLX SL-M7100 Rapidfire-Plus, 12s
Brakes	Shimano BR-MT420, Four piston, Rotor RT30 203 mm / 203 mm
Cassette	Shimano CS-M6100 12s 10/51
Pedals	Alu MTB Full+
Front Hub	Shimano TC500B, 15x110, CL, 32h / Glory Wheel, 15x110, CL, 32h
Rear Hub	Shimano TC500B, 12x148, CL, MicroSpline, 32h / Formula, 12x148, CL, MicroSplin
Rims	RADIALE X30, eDesign Asymmetric, Tubeless Ready, 622x30c
Stem	Satori Ursa, 35 mm, Internal routing
Handlebar	Alu, 780 mm, 35mm, Rise 15mm
Seatpost	Dropper Alpha 1, 31,6 mm, remote
Saddle	Whistle Performance
Tyres	Schwalbe Nobby Nic, Performance, Addix, 29"x2,60"

Motor	Smart System Perf. CX 36V, 250 W
Max Torque	85 Nm
Sensor Type	Torque
Battery	PowerTube 750 Horizontal, frametype, weight 4,2kg
Charger Type	4 A
Change Time	Up to 6 hours
Max Assisted Speed	25 km/h
Display	Kiox 300 + Led Remote
Power	Eco: 60 % Tour+: 60-340 % EMTB: 140-340 % Turbo: 340 %









-  Bosch Perf. CX Smart System
-  PowerTube 750Wh
-  Purion 200
-  29"
-  12s
-  27,5 kg

Black/ Silver	
40	0116862400
44	0116862410
48	0116862420
52	0116862430

Frame	Full Carbon 29", Toray T700, Integrated battery, Tapered, Internal routing, Rear travel 160 mm, 12x148 mm E-Thru
Fork	Rock Shox 35 Gold RL e-Bike, DebonAir, Motion Control, Lockout, 29", Travel 150 mm, 1.5 Tapered, Maxle Lite 15x110 mm
Rear Shock	Rock Shox Deluxe Select R, DebonAir, 230x65 mm
Headset	Acros for Ursa, 1,5", Internal routing
Crankset	Sram, 34T X-Sync2
Rear Derailleur	Sram SX Eagle, 12s
Shifters Levers	Sram SX Eagle Single Click Trigger, 12s
Brakes	Magura MT5, Four piston, Rotor RT30 203 mm / 203 mm
Cassette	Sram PG1210 Eagle 12s, 11/50
Pedals	Alu MTB Full+
Front Hub	Shimano TC500B, 15x110, CL, 32h / Glory Wheel, 15x110, CL, 32h
Rear Hub	Shimano TC500B, 12x148, CL, HG, 32h / Glory Wheel, 12x148, CL, HG, 32h
Rims	RADIALE X30, eDesign Asymmetric, Tubeless Ready, 622x30c
Stem	Satori Ursa, Barbore 35 mm
Handlebar	Alu, 780 mm, Barbore 35 mm, Rise 15mm
Seatpost	Dropper Alpha 1, 31,6 mm, remote
Saddle	Whistle Performance
Tyres	Schwalbe Nobby Nic, Performance, Addix, 29"x2,60"

Motor	Bosch Smart System Perf. CX 36 V, 250 W
Max Torque	85 Nm
Sensor Type	Torque
Battery	PowerTube 750 Horizontal, frametype, weight 4,2kg
Charger Type	4 A
Change Time	Up to 6 hours
Max Assisted Speed	25 km/h
Display	Purion 200
Power	Eco: 60 % Tour+: 60-340 % EMTB: 140-340 % Turbo: 340 %









-  Bosch Perf. CX Smart System
-  PowerTube 625Wh
-  Led Remote
-  29"
-  12s
-  26,9 kg

Black/ Silver	
40	0116862600
44	0116862610
48	0116862620
52	0116862630

Frame	Full Carbon 29", Toray T700, Integrated battery, Tapered, Internal routing, Rear travel 160 mm, 12x148 mm E-Thru
Fork	Rock Shox 35 Gold RL e-Bike, DebonAir, Motion Control, Lockout, 29", Travel 150 mm, 1.5 Tapered, Maxle Lite 15x110 mm
Rear Shock	Rock Shox Deluxe Select R, DebonAir, 230x65 mm
Headset	Acros for Ursa, 1.5", Internal routing
Crankset	FSA 34T
Rear Derailleur	Shimano Deore RD-M6100 SGS, Shadow Plus
Shifters Levers	Shimano Deore SL-M6100 Rapidfire-Plus, 12s
Brakes	Shimano BR-MT420, Four piston, Rotor SM-RT30 203 mm / 203 mm
Cassette	Shimano CS-M6100 12s 10/51
Pedals	Alu MTB Full+
Front Hub	Shimano TC500B, 15x110, CL, 32h / Glory Wheel, 15x110, CL, 32h
Rear Hub	Shimano TC500B, 12x148, CL, MicroSpline, 32h / Formula, 12x148, CL, MicroSplin
Rims	RADIALE X30, eDesign Asymmetric, Tubeless Ready, 622x30c
Stem	Satori Ursa, Barbore 35 mm
Handlebar	Alu, 780 mm, 35mm, Rise 15mm
Seatpost	Dropper Alpha 1, 31,6 mm, remote
Saddle	Whistle Performance
Tyres	Schwalbe Tough Tom 29", 2,6

Motor	Smart System Perf. CX 36 V, 250 W
Max Torque	85 Nm
Sensor Type	Torque
Battery	PowerTube 625 Horizontal, frametype, weight 3,5kg
Charger Type	4 A
Change Time	Up to 6 hours
Max Assisted Speed	25 km/h
Display	Led Remote
Power	Eco: 60 % Tour+: 60-340 % EMTB: 140-340 % Turbo: 340 %









-  OLI Edge
-  PowerTube 603Wh
-  Oli High Vision
-  29"
-  12s
-  25,2 kg

Black/White	
40	0116850950
44	0116850960
48	0116850970
52	0116850980

Frame	Full Carbon 29", Toray T700, integrated battery, Rear travel 150 mm, 12x148 mm E-Thru	Motor	OLI Edge 36 V, 250 W
Fork	Rock Shox Recon Silver RL, Solo Air, 29", Travel 150 mm, 1.5 Tapered, Maxle Lite 15x110 mm	Max Torque	90 Nm
Rear Shock	Rock Shox Deluxe Select R, DebonAir, 230x65 mm	Sensor Type	Torque
Headset	Acros for Ursa, 1.5", Internal routing	Battery	Phylion BN21L 603Wh, weight 3,6 kg
Crankset	FSA 34T	Charger Type	2 A
Rear Derailleur	Shimano XT RD-M8100 SGS, Shadow Plus	Change Time	Up to 9 hours
Shifters Levers	Shimano Deore SL-M6100 Rapidfire-Plus, 12s	Max Assisted Speed	25 km/h
Brakes	Shimano BR-MT420, Four piston, Rotor SM-RT30 203 mm / 203 mm	Display	Oli High Vision
Cassette	Shimano CS-M6100 12s 10/51	Power	Mode 1: 120% Mode 2: 180% Mode 3: 230% dynamic Mode 4: 400% dynamic
Pedals	Alu MTB Full+		
Front Hub	Shimano TC500B, 15x110, CL, 32h / Glory Wheel, 15x110, CL, 32h		
Rear Hub	Shimano TC500B, 12x148, CL, MicroSpline, 32h / Formula, 12x148, CL, MicroSpline, 32h		
Rims	RADIALE X30, eDesign Asymmetric, Tubeless Ready, 622x30c		
Stem	Alu, Barbore 31.8 mm		
Handlebar	Alu, 780 mm, Barbore 31.8, Rise 15 mm		
Seatpost	Dropper Alpha 1, 31,6 mm, remote		
Saddle	Whistle Performance		
Tyres	Schwalbe Tough Tom 29"x2,25" / Vittoria Barzo		



-  OLI Edge
-  PowerTube 603Wh
-  Oli High Vision
-  29"
-  10s
-  25,2 kg

Black/Yellow	
40	0116851000
44	0116851010
48	0116851020
52	0116851030

Frame	Full Carbon 29", Toray T700, integrated battery, Rear travel 150 mm, 12x148 mm E-Thru
Fork	RST Vibe TNL, Coil, Lockout, 29", Travel 140 mm, 1.5 Tapered, 15x110
Rear Shock	Rock Shox Deluxe Select R, DebonAir, 230x65 mm
Headset	Acros for Ursa, 1.5", Internal routing
Crankset	FSA 34T
Rear Derailleur	Shimano Deore RD-M5120, Shadow Plus, 10s
Shifters Levers	Shimano Deore SL-M4100 Rapidfire-Plus, 10s
Brakes	Shimano BR-MT200, Rotor SM-RT10 180 mm/180 mm
Cassette	Shimano CS-M4100, 10s, 11/46
Pedals	Alu MTB Full+
Front Hub	Shimano TC500B, 15x110, CL, 32h / Glory Wheel, 15x110, CL, 32h
Rear Hub	Shimano TC500B, 12x148, CL, HG, 32h / Glory Wheel, 12x148, CL, HG, 32h
Rims	RADIALE X30, eDesign Asymmetric, Tubeless Ready, 622x30c
Stem	Alu, Barbore 31.8 mm
Handlebar	Alu, 780 mm, Barbore 31.8, Rise 15 mm
Seatpost	Dropper Alpha 1, 31,6 mm, remote
Saddle	Whistle Performance
Tyres	Schwalbe Smart Sam, Performance, Addix, 29"x2.35" / Vittoria Barzo / Continental Mountain King

Motor	OLI Edge 36 V, 250 W
Max Torque	90 Nm
Sensor Type	Torque
Battery	Phylion BN21L 603Wh, weight 3,6 kg
Charger Type	2 A
Change Time	Up to 9 hours
Max Assisted Speed	25 km/h
Display	Oli High Vision
Power	Mode 1: 120% Mode 2: 180% Mode 3: 230% dynamic Mode 4: 400% dynamic

Estetica funzionalità e prestazioni.
Massimo controllo in discesa grazie
alla geometria raccolta,
pedalabilità in salita assicurata
dall'assistenza elettrica.

Aesthetic, features and
performance.

Maximum control in steep downhill
thanks to short geometry,
rideability in uphill allowed by the
electric power.



Interfaccia Gravity Casting

Telaio con interfaccia prodotta con il metodo della fusione per colata a gravità. Questa tecnologia permette di ottenere un componente estremamente compatto e resistente, migliorando la rigidità torsionale sotto gli sforzi di motore e ciclista.







Gravity Casting Interface

Frame with an interface produced by the gravity casting method.

This technology results in an extremely compact and strong component, improving torsional rigidity under engine and rider stresses





-  Bosch Perf. CX Smart System
-  PowerTube 750Wh
-  Purion 200
-  29"
-  12s
-  28,1







Red	
40	0116871400
44	0116871410
48	0116871420
52	0116871430
Petroleum	
40	0116863100
44	0116863110
48	0116863120
52	0116863130

Frame	Alu 29", Gravity casting, Integrated battery, Tapered, Internal routing, Rear travel 156 mm, 12x148 mm E-Thru
Fork	Rock Shox 35 Gold RL e-Bike, DebonAir, Motion Control, Lockout, 29", Travel 150 mm, 1.5 Tapered, Maxle Lite 15x110 mm
Rear Shock	Rock Shox Deluxe Select R, DebonAir, 230x65 mm
Headset	Acros for Ursa, 1.5", Internal routing
Crankset	FSA 34T, Megatooth
Rear Derailleur	Shimano Deore RD-M6100 SGS Shadow Plus, 12s
Shifters Levers	Shimano Deore SL-M6100 Rapidfire-Plus, 12s
Brakes	Shimano BR-MT420, Four piston, Rotor SM-RT30 203 mm / 203 mm
Cassette	Shimano CS-M6100, 12s, 10/51
Pedals	Alu MTB Full+
Front Hub	Shimano TC500B, 15x110, CL, 32h / Glory Wheel, 15x110, CL, 32h
Rear Hub	Shimano TC500B, 12x148, CL, MicroSpline, 32h / Formula, 12x148, CL, MicroSpline, 32h
Rims	RADIALE X30, eDesign Asymmetric, Tubeless Ready, 622x30c
Stem	Alu, Barbore 35 mm
Handlebar	Alu, 780 mm, Barbore 35mm, Rise 15mm
Seatpost	Dropper Alpha1, 31,6 mm, remote
Saddle	Whistle Performance
Tyres	Schwalbe Nobby Nic, Performance, Addix, 29"x2,60"

Motor	Bosch Smart System Perf. CX 36 V, 250 W
Max Torque	85 Nm
Sensor Type	Torque
Battery	PowerTube 750 Horizontal, frametype, weight 4,2kg
Charger Type	4 A
Change Time	Up to 6 hours
Max Assisted Speed	25 km/h
Display	Purion 200
Power	Eco: 60 % Tour+: 60-340 % EMTB: 140-340 % Turbo: 340 %











-  Bosch Perf. CX Smart System
-  PowerTube 750Wh
-  Purion 200
-  29"
-  12s
-  28,1 kg

Petroleum	
40	0116871500
44	0116871510
48	0116871520
52	0116871530

Frame	Alu 29", Gravity casting, Integrated battery, Tapered, Internal routing, Rear travel 156 mm, 12x148 mm E-Thru
Fork	Rock Shox 35 Silver TK e-Bike, Solo Air, Lockout, 29", Travel 150 mm, 1.5 Tapered, Maxle Lite 15x110 mm
Rear Shock	Rock Shox Deluxe Select R, DebonAir, 230x65 mm
Headset	Acros for Ursa, 1.5", Internal routing
Crankset	Sram, 34T X-Sync2
Rear Derailleur	Sram SX Eagle, 12s
Shifters Levers	Sram SX Eagle, 12s Single Click Trigger, 12s
Brakes	Shimano BR-MT420, Four piston, Rotor SM-RT30 203 mm / 203 mm
Cassette	Sram PG1210 Eagle, 12s, 11/50
Pedals	Alu MTB Full+
Front Hub	Shimano TC500B, 15x110, CL, 32h / Glory Wheel, 15x110, CL, 32h
Rear Hub	Shimano TC500B, 12x148, CL, HG, 32h / Glory Wheel, 12x148, CL, HG, 32h
Rims	RADIALE X30, eDesign Asymmetric, Tubeless Ready, 622x30c
Stem	Alu, Barbore 35 mm
Handlebar	Alu, 780 mm, Barbore 35mm, Rise 15mm
Seatpost	Dropper Alpha1, 31,6 mm, remote
Saddle	Whistle Performance
Tyres	Schwalbe Nobby Nic, Performance, Addix, 29"x2,60"

Motor	Bosch Smart System Perf. CX 36 V, 250 W
Max Torque	85 Nm
Sensor Type	Torque
Battery	PowerTube 750 Horizontal, frametype, weight 4,2kg
Charger Type	4 A
Change Time	Up to 6 hours
Max Assisted Speed	25 km/h
Display	Purion 200
Power	Eco: 60 % Tour+: 60-340 % EMTB: 140-340 % Turbo: 340 %









-  Bosch Perf. CX Smart System
-  PowerTube 625Wh
-  Led Remote
-  29"
-  12s
-  27,5 kg

Red	
40	0116871600
44	0116871610
48	0116871620
52	0116871630

Frame	Alu 29", Gravity casting, Integrated battery, Tapered, Internal routing, Rear travel 156 mm, 12x148 mm E-Thru
Fork	Rock Shox 35 Silver TK e-Bike, Solo Air, Lockout, 29", Travel 150 mm, 1.5 Tapered, Maxle Lite 15x110 mm
Rear Shock	Rock Shox Deluxe Select R, DebonAir, 230x65 mm
Headset	Acros for Ursa, 1.5", Internal routing
Crankset	FSA 34T
Rear Derailleur	Shimano Deore RD-M6100 SGS, Shadow Plus, 12s
Shifters Levers	Shimano Deore SL-M6100 Rapidfire-Plus, 12s
Brakes	Shimano BR-MT420, Four piston, Rotor SM-RT30 203 mm / 203 mm
Cassette	Shimano CS-M6100 12s 10/51
Pedals	Alu MTB Full+
Front Hub	Shimano TC500B, 15x110, CL, 32h / Glory Wheel, 15x110, CL, 32h
Rear Hub	Shimano TC500B, 12x148, CL, MicroSpline, 32h / Formula, 12x148, CL, MicroSpline, 32h
Rims	RADIALE X30, eDesign Asymmetric, Tubeless Ready, 622x30c
Stem	Alu, Barbore 35 mm
Handlebar	Alu, 780 mm, 35mm, Rise 15mm
Seatpost	Dropper Alpha1, 31,6 mm, remote
Saddle	Whistle Performance
Tyres	Schwalbe Nobby Nic, Performance, Addix, 29"x2.60"

Motor	Bosch Smart System Perf. CX 36 V, 250 W
Max Torque	85 Nm
Sensor Type	Torque
Battery	PowerTube 625 Horizontal, frametype, weight 3,5kg
Charger Type	2 A
Change Time	Up to 9 hours
Max Assisted Speed	25 km/h
Display	Led Remote
Power	Eco: 60 % Tour+: 60-340 % EMTB: 140-340 % Turbo: 340 %



-  Bosch Perf. CX Smart System
-  PowerTube 625Wh
-  Led Remote
-  29"
-  10s
-  27,7







Petroleum	
40	0116871700
44	0116871710
48	0116871720
52	0116871730
Red	
40	0116871800
44	0116871810
48	0116871820
52	0116871830

Frame	Alu 29", Gravity casting, Integrated battery, Tapered, Internal routing, Rear travel 156 mm, 12x148 mm E-Thru
Fork	RST Vibe TNL, Coil, Lockout, 29", Travel 140 mm, 1.5 Tapered, 15x110
Rear Shock	Rock Shox Deluxe Select R, DebonAir, 230x65 mm
Headset	Acros for Ursa, 1.5", Internal routing
Crankset	FSA 34T
Rear Derailleur	Shimano CUES RD-U6000 Shadow, 10s
Shifters Levers	Shimano CUES SL-U6000 Rapidfire Plus, 10s
Brakes	Shimano BR-MT420, Four piston, Rotor SM-RT30 203 mm / 203 mm
Cassette	Shimano CUES CS-LG300, 10s, 11/48
Pedals	Alu MTB Full+
Front Hub	Shimano TC500B, 15x110, CL, 32h / Glory Wheel, 15x110, CL, 32h
Rear Hub	Shimano TC500B, 12x148, CL, HG, 32h / Glory Wheel, 12x148, CL, HG, 32h
Rims	RADIALE X30, eDesign Asymmetric, Tubeless Ready, 622x30c
Stem	Alu, Barbore 35 mm
Handlebar	Alu, 780 mm, Barbore 35mm, Rise 15mm
Seatpost	Dropper Alpha1, 31,6 mm, remote
Saddle	Whistle Performance
Tyres	Schwalbe Nobby Nic, Performance, Addix, 29"x2,60"

Motor	Bosch Smart System Perf. CX 36 V, 250 W
Max Torque	85 Nm
Sensor Type	Torque
Battery	PowerTube 625 Horizontal, frametype, weight 3,5kg
Charger Type	2 A
Change Time	Up to 9 hours
Max Assisted Speed	25 km/h
Display	Led Remote
Power	Eco: 60 % Tour+: 60-340 % EMTB: 140-340 % Turbo: 340 %





-  Bosch Perf. CX
-  PowerTube 625Wh
-  Purion
-  29"
-  12s
-  26,8 kg

Dark Blue/Chrome	
40	0116850800
44	0116850810
48	0116850820
52	0116850830

Frame	Alu, 29", Hydroformed, Integrated battery, Rear travel 150 mm, 12x148 mm E-Thru
Fork	Rock Shox Recon Silver RL, Solo Air, 29", Travel 150 mm, 1.5 Tapered, Maxle Lite 15x110 mm
Rear Shock	Rock Shox Monarch R, SoloAir, 200x57 mm
Headset	FSA No.57B tapered 1"1/2
Crankset	FSA, 34T, Megatooth
Rear Derailleur	Sram SX Eagle, 12s
Shifters Levers	Sram SX Eagle, 12s Single Click Trigger, 12s
Brakes	Shimano BR-MT420, Four piston, Rotor SM-RT30 203 mm / 203 mm
Cassette	Sram PG1210 Eagle 12s, 11/50
Pedals	Alu MTB Full
Front Hub	Shimano TC500B, 15x110, CL, 32h / Glory Wheel, 15x110, CL, 32h
Rear Hub	Shimano TC500B, 12x148, CL, HG, 32h / Glory Wheel, 12x148, CL, HG, 32h
Rims	Radiale X25, eDesign Asymmetric, Tubeless Ready, 622x25c
Stem	Alu, Barbore 31,8 mm
Handlebar	Alu, 780 mm, 31,8mm, Rise 15mm
Seatpost	Dropper Alpha1, 31,6 mm, remote
Saddle	Whistle Performance
Tyres	Schwalbe Nobby Nic, Performance, Addix, 29"x2.60"

Motor	Bosch Performance CX 36V, 250 W
Max Torque	85 Nm
Sensor Type	Torque
Battery	PowerTube 625 Horizontal, frametype, weight 3,5 kg
Charger Type	2 A
Change Time	Up to 9 hours
Max Assisted Speed	25 km/h
Display	Purion
Power	Eco: 60 % Tour+: 60-340 % EMTB: 140-340 % Turbo: 340 %







E-HardTail

Percorsi sterrati, salite da affrontare con agilità, discese impegnative.
Le nostre eMTB Hardtail sono perfette per affrontare ogni tipo di trail.

Dirt panths, agility climb, demanding descents.
Our Hardtail eMtb are perfect for all types of trails.











-  Bosch Perf. Line CX Smart System
-  PowerTube 750Wh
-  Kiox 300 + Led Remote
-  29"
-  12s
-  24,7 kg

Carbon/Orange	
40	0116851300
46	0116851310
52	0116851320

Frame	Full Carbon 29", Toray T700, Integrated battery, Tapered, Integrated cables, 12x148 mm E-Thru
Fork	RST Vibe TNL, Coil, Lockout, Travel 120 mm, 1.5 Tapered, 15x110 mm
Headset	Acros for Viper, 1.5", Internal routing
Crankset	FSA 34T, Megatooth
Rear Derailleur	Shimano XT RD-M8100 SGS Shadow Plus, 12s
Shifters Levers	Shimano XT SL-M8100 Rapidfire-Plus, 12s
Brakes	Shimano BR-MT420, Four piston, Rotor RT30 203 mm / 203 mm
Cassette	Shimano CS-M6100 12s 10/51
Pedals	Alu MTB
Front Hub	Shimano TC500B, 15x110, CL, 32h / Glory Wheel, 15x110, CL, 32h
Rear Hub	Shimano TC500B, 12x148, CL, MicroSpline, 32h / Formula, 12x148, CL, MicroSpline, 32h
Rims	Radiale X30, eDesign Asymmetric, Tubeless Ready, 622x30c
Stem	Satori Viper0, 31,8 mm, Internal routing
Handlebar	Alu, 720 mm, Barbore 31.8, Rise 25 mm
Seatpost	Dropper Alpha1, 31,6 mm, remote
Saddle	Selle Royal Sauris
Tyres	Schwalbe Smart Sam, Performance, Addix, 29"x2,35"

Motor	Bosch Smart System Perf. Line CX 36 V, 250 W
Max Torque	85 Nm
Sensor Type	Torque
Battery	PowerTube 750 Horizontal, frametype, weight 4,2 kg
Charger Type	4 A
Change Time	Up to 9 hours
Max Assisted Speed	25 km/h
Display	Kiox 300 + Led Remote
Power	Eco: 60 % Tour+: 60-340 % EMTB: 140-340 % Turbo: 340 %









-  Bosch Perf. Line CX Smart System
-  PowerTube 750Wh
-  Led Remote
-  29"
-  12s
-  24,1 kg

Carbon/Orange	
40	0116851350
46	0116851360
52	0116851370

Frame	Full Carbon 29", Toray T700, Integrated battery, Tapered, Integrated cables, 12x148 mm E-Thru
Fork	RST Vibe TNL, Coil, Lockout, Travel 120 mm, 1.5 Tapered, 15x110 mm
Headset	Acros for Viper, 1.5", Internal routing
Crankset	FSA 34T, Megatooth
Rear Derailleur	Shimano Deore RD-M6100 SGS Shadow Plus, 12s
Shifters Levers	Shimano Deore SL-M6100 Rapidfire-Plus, 12s
Brakes	Shimano BR-MT420, Four piston, Rotor RT30 203 mm / 203 mm
Cassette	Shimano CS-M6100 12s 10/51
Pedals	Alu MTB
Front Hub	Shimano TC500B, 15x110, CL, 32h /Glory Wheel, 15x110, CL, 32h
Rear Hub	Shimano TC500B, 12x148, CL, MicroSpline, 32h /Formula, 12x148, CL, MicroSpline, 32h
Rims	Radiale X30, eDesign Asymmetric, Tubeless Ready, 622x30c
Stem	Satori Viper0, 31,8 mm, Internal routing
Handlebar	Alu, 720 mm, Barbore 31.8, Rise 25 mm
Seatpost	Dropper Alpha1, 31,6 mm, remote
Saddle	Selle Royal Sauris
Tyres	Schwalbe Smart Sam, Performance, Addix, 29"x2,35"

Motor	Bosch Smart System Perf. Line CX 36 V, 250 W
Max Torque	85 Nm
Sensor Type	Torque
Battery	PowerTube 750 Horizontal, frametype, weight 4,2 kg
Charger Type	4 A
Change Time	Up to 9 hours
Max Assisted Speed	25 km/h
Display	Led Remote
Power	Eco: 60 % Tour+: 60-340 % EMTB: 140-340 % Turbo: 340 %

-  OLI Edge
-  Phyllion 603Wh
-  Oli High Vision
-  29"
-  10s
-  23,7 kg









Carbon/ Blue	
40	0116851253
46	0116851263
50	0116851273
Carbon / Red	
40	0116851250
46	0116851260
50	0116851270

Frame	Full Carbon 29", Toray T700, Integrated battery, Tapered, Integrated cables, 12x148 mm E-Thru
Fork	RST Vibe TNL, Coil, Lockout, Travel 120 mm, 1.5 Tapered, 15x110mm / Suntour XCR34, Coil, Lockout, Travel 120 mm, 1.5 Tapered, 15x110 mm, remote
Headset	Acros for Viper, 1.5", Internal routing
Crankset	FSA, 34T, Megatooth
Rear Derailleur	Shimano Deore RD-M4100 SGS, Shadow Plus
Shifters Levers	Shimano Deore SL-M4100 Rapidfire-Plus, 10s
Brakes	Shimano BR-MT200, Rotor SM-RT30 180 mm/180 mm
Cassette	Shimano CS-M1100 10s 11/46
Pedals	Alu MTB
Front Hub	Shimano TC500B, 15x110, CL, 32h / Glory Wheel, 15x110, CL, 32h
Rear Hub	Shimano TC500B, 12x148, CL, HG, 32h / Glory Wheel, 12x148, CL, HG, 32h
Rims	RADIALE E25, eBike Ready, Tubeless Ready, 622x25c
Stem	Satori Viper 0, Barbore 31.8 mm, Internal routing
Handlebar	Alu, 720 mm, Barbore 31,8, Rise 25 mm
Seatpost	Alu, 31,6 mm
Saddle	Selle Royal Sauris
Tyres	Schwalbe Smart Sam, Performance, Addix, 29"x2,35"

Motor	OLI Edge 36 V, 250 W
Max Torque	90 Nm
Sensor Type	Torque
Battery	Phyllion BN21L 603Wh, weight 3,6 kg
Charger Type	2 A
Charge Time	Up to 9 hours
Max Assisted Speed	25 km/h
Display	Oli High Vision
Power	Mode 1: 120% Mode 2: 180% Mode 3: 230% dynamic Mode 4: 400% dynamic











-  Bosch Perf. Line CX Smart System
-  PowerTube 750Wh
-  Led Remote
-  29"
-  12s
-  26,3 kg

Anthracite/Gold	
40	0116867500
46	0116867510
52	0116867520

Frame	Alu, 29", Gravity Casting, Integrated battery, Internal routing, 12x148 mm E-Thru
Fork	Suntour XCR32-Boost, Coil, Lockout, 29", Travel 120 m, 1.5 Tapered, 15x110
Headset	Acros for Viper, 1.5", Internal routing
Crankset	FSA 34T, Megatooth
Rear Derailleur	Shimano Deore RD-M6100 SGS Shadow Plus, 12s
Shifters Levers	Shimano Deore SL-M6100 Rapidfire-Plus, 12s, I-spec
Brakes	Shimano BR-MT200, Rotor SM-RT30 180 mm / 180 mm
Cassette	Shimano CS-M6100 12s 10/51
Pedals	Alu MTB
Front Hub	Shimano TC500B, 15x110, CL, 32h / Glory Wheel, 15x110, CL, 32h
Rear Hub	Shimano TC500B, 12x148, CL, MicroSpline, 32h / Formula, 12x148, CL, MicroSpline, 32h
Rims	RADIALE E25, eBike Ready, Tubeless Ready, 622x25c
Stem	Satori Viper0, 31,8 mm, Internal routing
Handlebar	Alu, 720 mm, Barbore 31.8, Rise 25 mm
Seatpost	Dropper Alpha1, 31,6 mm, remote
Saddle	Selle Royal Sauris
Tyres	Schwalbe Smart Sam, Performance, Addix, 29"x2.35" / Vittoria Barzo
Chaincover	FSA Bash guard

Motor	Bosch Smart System Perf. Line CX 36 V, 250 W
Max Torque	85 Nm
Sensor Type	Torque
Battery	PowerTube 750 Horizontal, frametype, weight 4,2 kg
Charger Type	4 A
Change Time	Up to 6 hours
Max Assisted Speed	25 km/h
Display	Led Remote
Power	Eco: 60 % Tour+: 60-340 % EMTB: 140-340 % Turbo: 340 %

-  Bosch Perf. Line CX Smart System
-  PowerTube 625Wh
-  Led Remote
-  29"
-  10s
-  25,7 kg

Green/Red	
40	0116867800
46	0116867810
52	0116867820
Silver/Red	
40	0116867700
46	0116867710
52	0116867720









Frame	Alu 29", Gravity casting, Integrated battery, Tapered, Internal routing, 12x148 mm E-Thru
Fork	Suntour XCM, Coil, Lokout, 29", Travel 100 mm, QR / Zoom 860 AMS, Travel 100
Headset	Acros for Viper, 1.5", Internal routing
Crankset	FSA 34T
Rear Derailleur	Shimano CUES RD-U6000 GS Shadow, 10s
Shifters Levers	Shimano CUES SL-U6000 Rapidfire Plus, 10s
Brakes	Shimano BR-MT200, Rotor SM-RT30 180 mm / 180 mm
Cassette	Shimano CUES CS-LG300, 10s, 11/48
Pedals	Alu MTB
Front Hub	Shimano TC500B, 15x110, CL, 32h / Glory Wheel, 15x110, CL, 32h
Rear Hub	Shimano TC500B, 12x148, CL, HG, 32h / Glory Wheel, 12x148, CL, HG, 32h
Rims	RADIALE E25, eBike Ready, Tubeless Ready, 622x25c
Stem	Satori Viper0, 31,8 mm, Internal routing
Handlebar	Alu, 720 mm, Barbore 31.8, Rise 25 mm
Seatpost	Dropper Alpha1, 31,6 mm, remote
Saddle	Selle Royal Sauris
Tyres	Schwalbe Tough Tom, Active Line, 29"x2.35" / Vittoria Barzo
Chaincover	FSA Bash Guard

Motor	Bosch Smart System Perf. Line CX 36 V, 250 W
Max Torque	85 Nm
Sensor Type	Torque
Battery	PowerTube 625 Horizontal, frametype, weight 3,5 kg
Charger Type	2 A
Change Time	Up to 6 hours
Max Assisted Speed	25 km/h
Display	Led Remote
Power	Eco: 60 % Tour+: 60-340 % EMTB: 140-340 % Turbo: 340 %





-  Bosch Performance CX
-  PowerTube 625Wh
-  Purion
-  29"
-  9s
-  23,8 kg

Man: Blue	
46	0115307250
50	0115307260







Lady: Blue	
40	0115307200
46	0115307210

Frame	Alu 29", Hydroformed, Integrated battery, Tapered, External routing, Forged interface, QR
Fork	Zoom 860 AMS, Coil, Lockout, 29", Travel 100 mm, QR
Headset	FSA No.57BP-1
Crankset	Miche 34T
Rear Derailleur	Sram Rear Derailleur, X5 9s
Shifters Levers	Sram Shifter Lever X5 Multiple click, 9s
Brakes	Shimano BR-MT200, Rotor SM-RT10 180 mm / 180 mm
Cassette	Sram Cassette PG-920, 9s, 11/34
Pedals	Alu MTB
Front Hub	Shimano TX505, CL, 32h
Rear Hub	Shimano TX505, CL, HG, 32h
Rims	RADIALE E25, eBike Ready, Tubeless Ready, 622x25c
Stem	Alu, Barbore 31.8 mm
Handlebar	Alu, 720 mm, Barbore 31.8, Rise 25 mm
Seatpost	Alu, 31,6 mm
Saddle	Selle Royal Sauris
Tyres	Vittoria Barzo 29"x2.10"
Chaincover	FSA Bash Guard

Motor	Bosch Performance CX 36 V, 250 W
Max Torque	85 Nm
Sensor Type	Torque
Battery	PowerTube 625 Horizontal, frametype, weight 3,5 kg
Charger Type	4 A
Change Time	Up to 5 hours
Max Assisted Speed	25 km/h
Display	Purion
Power	Eco: 60 % Tour+: 60-340 % EMTB: 140-340 % Turbo: 340 %











-  Bosch Perf. CX Smart System
-  PowerTube 500Wh
-  Led Remote
-  29"
-  10s
-  25,3 kg

Anthracite/Gold	
46	0116863705
52	0116863715

Frame	Alu, 29", Gravity Casting, Integrated battery, Internal routing, Forged interface, 12x148 mm E-Thru
Fork	Zoom 860 AMS, Coil, Lockout, 29", Travel 100 mm, QR
Headset	Acros for Viper, 1.5", Internal routing
Crankset	Miche 34T
Rear Derailleur	Shimano Deore RD-4120 Shadow Plus, 10s
Shifters Levers	Shimano Deore SL-M4100 Rapidfire-Plus, 10s
Brakes	Shimano BR-MT200, Rotor SM-RT30 180 mm / 180 mm
Cassette	Shimano CS-M1100, 10s, 11/42
Pedals	Alu MTB
Front Hub	Shimano TX505, CL, 32h
Rear Hub	Shimano TC500B, 12x148, CL, HG, 32h / Glory Wheel, 12x148, CL, HG, 32h
Rims	RADIALE E25, eBike Ready, Tubeless Ready, 622x25c
Stem	Satori Viper0, 31,8 mm, Internal routing
Handlebar	Alu, 720 mm, Barbore 31.8, Rise 25 mm
Seatpost	Dropper Alpha1, 31,6 mm, remote
Saddle	Selle Royal Sauris
Tyres	Vittoria Barzo 29"x2.25"
Chaincover	FSA Bash Guard

Motor	Bosch Smart System Perf. CX 36 V, 250 W
Max Torque	85 Nm
Sensor Type	Torque
Battery	PowerTube 500 Horizontal, frametype, weight 3,65 kg
Charger Type	4 A
Change Time	Up to 7 hours
Max Assisted Speed	25 km/h
Display	Led Remote
Power	Eco: 60 % Tour+: 60-340 % EMTB: 140-340 % Turbo: 340 %









-  Bosch Perf. CX Smart System
-  PowerTube 500Wh
-  Led Remote
-  29"
-  10s
-  25,3 kg

Light Blue	
40	0115328550
46	0115328560

Frame	Alu 29", Gravity casting, Integrated battery, Tapered, Internal routing, 12x148 mm E-Thru
Fork	Zoom 860 AMS, Coil, Lockout, 29", Travel 100 mm, QR
Headset	Acros universal, 1,5", Internal routing
Crankset	Miche 34T
Rear Derailleur	Shimano Deore RD-4120 Shadow Plus, 10s
Shifters Levers	Shimano Deore SL-M4100 Rapidfire-Plus, 10s
Brakes	Shimano BR-MT200, Rotor SM-RT30 180 mm / 180 mm
Cassette	Shimano CS-M1100, 10s, 11/42
Pedals	Alu MTB
Front Hub	Shimano TX505, CL, 32h
Rear Hub	Shimano TX505, CL, HG, 32h
Rims	RADIALE E25, eBike Ready, Tubeless Ready, 622x25c
Stem	Alu, Barbore 31.8 mm
Handlebar	Alu, 720 mm, Barbore 31.8, Rise 25 mm
Seatpost	Dropper Alpha1, 31,6 mm, remote
Saddle	Selle Royal Sauris
Tyres	Vittoria Barzo 29"x2.25"
Chaincover	FSA Bash Guard

Motor	Bosch Smart System Perf. CX 36 V, 250 W
Max Torque	85 Nm
Sensor Type	Torque
Battery	PowerTube 500 Horizontal, frametype, weight 3,65 kg
Charger Type	4 A
Change Time	Up to 7 hours
Max Assisted Speed	25 km/h
Display	Led Remote
Power	Eco: 60 % Tour+: 60-340 % EMTB: 140-340 % Turbo: 340 %









-  Bosch Performance Line
-  PowerTube 625Wh
-  Purion
-  29"
-  10s
-  23,5 kg

Light Blue	
40	0115328500
46	0115328510

Frame	Alu 29", Hydroformed, Integrated battery, Tapered, External routing, Forged interface, QR
Fork	Zoom 860 AMS, Coil, Lockout, 29", Travel 100 mm, QR
Headset	Acros universal, 1,5", Internal routing
Crankset	Miche 34T
Rear Derailleur	Shimano Deore RD-4120 Shadow Plus, 10s
Shifters Levers	Shimano Deore SL-M4100 Rapidfire-Plus, 10s
Brakes	Shimano BR-MT200, Rotor SM-RT10 180 mm / 180 mm
Cassette	Shimano CS-M1100, 10s, 11/42
Pedals	Alu MTB
Front Hub	Shimano TX505, CL, 32h
Rear Hub	Shimano TX505, CL, HG, 32h
Rims	RADIALE E25, eBike Ready, Tubeless Ready, 622x25c
Stem	Alu, Barbore 31.8 mm
Handlebar	Alu, 720 mm, Barbore 31.8, Rise 25 mm
Seatpost	Alu, 31,6 mm
Saddle	Selle Royal Sauris
Tyres	Vittoria Barzo 29"x2.25"
Chaincover	FSA Bash Guard

Motor	Bosch Performance Line 36V, 250 W
Max Torque	85 Nm
Sensor Type	Torque
Battery	PowerTube 625 Horizontal, frametype, weight 3,5 kg
Charger Type	2 A
Change Time	Up to 9 hours
Max Assisted Speed	25 km/h
Display	Purion
Power	Eco: 60 % Tour+: 60-340 % EMTB: 140-340 % Turbo: 340 %









-  AM80
-  EnergyTube 540Wh
-  AM LCD FullColour
-  29"
-  12s
-  24,8 kg

Flat Grey/Neon Red	
40	0116832600
46	0116832610
52	0116832620

Frame	Alu 29", Hydroformed, internal battery, Tapered, Internal routing, Forged interface, QR
Fork	Suntour XCR32, Coil, 29", Travel 100, 1.5 Tapered, QR /Zoom 860 AMS, Travel 100
Headset	Acros for Viper, 1.5", Internal routing
Crankset	FSA, 34T, Megatooth
Rear Derailleur	Sram SX Eagle
Shifters Levers	Sram SX Eagle Single Click Trigger, 12s
Brakes	Clarks M4, Rotor SM-RT10 180mm/180mm
Cassette	Sram PG1210 Eagle 12s, 11/50
Pedals	Alu MTB
Front Hub	Shimano TX505, CL, 32h
Rear Hub	Shimano TX505, CL, HG, 32h
Rims	RADIALE E25, eBike Ready, Tubeless Ready, 622x25c
Stem	Satori Viper0, 31,8 mm, Internal routing
Handlebar	Alu, 720 mm, Barbore 31.8, Rise 25 mm
Seatpost	Alu, 30,4 mm
Saddle	Selle Royal Sauris
Tyres	Schwalbe Smart Sam, Performance, Addix, 29"x2,35" / Vittoria Barzo
Chaincover	FSA Bash Guard

Motor	AM-80 36 V, 250 W
Max Torque	80 Nm
Sensor Type	Torque
Battery	EnergyTube 540, frametype, weight 2,9 kg
Charger Type	2 A
Change Time	Up to 7 hours
Max Assisted Speed	25 km/h
Display	AM LCD Full-Colour
Power	Mode 1: 50 % Mode 2: 100 % Mode 3: 200 % Mode 4: 300 % Mode 5: 400%



-  AM80
-  EnergyTube 540Wh
-  AM LCD FullColour
-  29"
-  12s
-  24,8 kg







Anthracite/Black Matt	
40	0115296400
46	0115296410
52	0115296420

Frame	Alu 29", Hydroformed, Integrated battery, Tapered, Internal routing, Forged interface, QR
Fork	Suntour XCR32, Coil, 29", Travel 100, 1.5 Tapered, QR / Zoom 860 AMS, Travel 100
Headset	Acros for Viper, 1.5", Internal routing
Crankset	FSA, 34T, Megatooth
Rear Derailleur	Sram SX Eagle
Shifters Levers	Sram SX Eagle Single Click Trigger, 12s
Brakes	Clarks M4, Rotor SM-RT10 180mm/180mm
Cassette	Sram PG1210 Eagle 12s, 11/50
Pedals	Alu MTB
Front Hub	Shimano TX505, CL, 32h
Rear Hub	Shimano TX505, CL, HG, 32h
Rims	RADIALE E25, eBike Ready, Tubeless Ready, 622x25c
Stem	Satori Viper0, 31,8 mm, Internal routing
Handlebar	Alu, 720 mm, Barbore 31.8, Rise 25 mm
Seatpost	Alu, 30,4 mm
Saddle	Selle Royal Sauris
Tyres	Schwalbe Smart Sam, Performance, Addix, 29"x2,35" / Vittoria Barzo
Chaincover	FSA Bash Guard

Motor	AM-80 36 V, 250 W
Max Torque	80 Nm
Sensor Type	Torque
Battery	EnergyTube 540, frametype, weight 2,9 kg
Charger Type	2 A
Change Time	Up to 7 hours
Max Assisted Speed	25 km/h
Display	AM LCD Full-Colour
Power	Mode 1: 50 % Mode 2: 100 % Mode 3: 200 % Mode 4: 300 % Mode 5: 400%

Atala B-Cross A3.2X LT10



-  AM80
-  EnergyTube 540Wh
-  AM LCD
-  29"
-  10s
-  23,5 kg







Anthracite/Black Matt	
42	0115296454
46	0115296464
50	0115296474

Frame	Alu 29", hydroformed, integrated battery, tapered, Internal routing, Forged interface, QR
Fork	Zoom 862S AMS, 100 mm, Tapered, Coil
Headset	Acros AZF-576, 1,5", Internal routing
Crankset	Miranda, 34T
Rear Derailleur	LT, RD-V5010-LX, 10s
Shifters Levers	LT, SL-V5010-10, 10s
Brakes	Shimano BR-MT200, Rotor SM-RT10 180mm/180 mm
Cassette	LT, CS-A7, 10s, 11-46T
Pedals	Alu MTB
Front Hub	FastAce, DA210FSS1, 15x100 32h, CL
Rear Hub	Shimano TX505, CL, HG, 32h
Rims	RADIALE E25, eBike Ready, Tubeless Ready, 622x25c
Stem	Satori Viper0, 31,8 mm, Internal routing
Handlebar	Alu Low Rise, 720 mm
Seatpost	Alu, 30,4 mm
Saddle	Selle Royal Mach
Tyres	Vittoria Barzo

Motor	AM-80 36 V, 250 W
Max Torque	80 Nm
Sensor Type	Torque
Battery	EnergyTube 540, frametype, weight 2,9 kg
Charger Type	2 A
Change Time	Up to 7 hours
Max Assisted Speed	25 km/h
Display	AM LCD
Power	Mode 1: 50 % Mode 2: 100 % Mode 3: 200 % Mode 4: 300 % Mode 5: 400%

Atala B-Cross A3.4 LT10









-  AM80
-  EnergyTube 540Wh
-  AM LCD
-  29"
-  10s
-  23,5 kg

Anthracite/Black Matt	
42	0115296455
46	0115296465
50	0115296475

Frame	Alu 29", hydroformed, integrated battery, tapered, Internal routing, Forged interface
Fork	Zoom 860 AMS, 100 mm, Steerer, Coil
Headset	Acros for Viper, 1.5", Internal routing
Crankset	Miranda, 34T
Rear Derailleur	LT, RD-V5010-LX, 10s
Shifters Levers	LT, SL-V5010-10, 10s
Brakes	Clarks M2, Rotor SM-RT10 180mm/180mm
Cassette	LT, CS-A7, 10s, 11-46T
Pedals	Alu MTB
Front Hub	Shimano TX505, CL, 32h / Formula CL-51, QR, CL, 32h
Rear Hub	Shimano TX505, CL, HG, 32h / Formula CL-52, QR, CL, HG, 32h
Rims	RADIALE E25, eBike Ready, Tubeless Ready, 622x25c
Stem	Satori Viper0, 31,8 mm, Internal routing
Handlebar	Alu Low Rise, 720 mm
Seatpost	Alu, 30,4 mm
Saddle	Selle Royal Mach
Tyres	Schwalbe Rapid Rob, 29"x2.25" / Vittoria Barzo
Chaincover	FSA Bash Guard

Motor	AM-80 36 V, 250 W
Max Torque	80 Nm
Sensor Type	Torque
Battery	EnergyTube 540, frametype, weight 2,9 kg
Charger Type	2 A
Change Time	Up to 7 hours
Max Assisted Speed	25 km/h
Display	AM LCD
Power	Mode 1: 50 % Mode 2: 100 % Mode 3: 200 % Mode 4: 300 % Mode 5: 400%

-  Yamaha PS-X1X3 ST
-  400Wh
-  Display A
-  29"
-  10s
-  21,6 kg

Black	
42	0115307600
46	0115307610
50	0115307620



Frame	Alu 29", Hydroformed, downtube battery, Tapered, External Routing, Forged Interface, quick-relise
Fork	Zoom 860 AMS, 100 mm, Straight, Coil
Headset	FSA No.57BP-1
Crankset	Miche 34T
Rear Derailleur	LT, RD-V5010-LX, 10s
Shifters Levers	LT, SL-V5010-10, 10s
Brakes	Clarks M2, Rotor 180mm/180mm
Cassette	LT, CS-A7, 10s, 11-46T
Pedals	Alu MTB
Front Hub	Shimano TX505, CL, 32h
Rear Hub	Shimano TX505, CL, 32h
Rims	Radiale E25, eBike Ready, Tubeless Ready, 622x25c
Stem	Alu, Bar bore 31,8 mm
Handlebar	Alu, 720 mm, 31,8 mm, Rise 25 mm
Seatpost	Alu, 31,6 mm
Saddle	Selle Royal Sauris
Tyres	Schwalbe Smart Sam, Performance,, 27,5"x2,35"
Chaincover	FSA Bash Guard

Motor	Yamaha Pwseries ST 250 W, 36V
Max Torque	70 Nm
Sensor Type	Torque
Battery	External on downtube, DT400
Charger Type	4 A
Change Time	Up to 3,5 hours
Max Assisted Speed	25 km/h
Display	Display A
Power	+Eco: 50% Eco: 100% Standard: 190% High-Performance: 280%







E-Gravel

Scegliere i tuoi itinerari senza doverli pianificare, affrontando sia sentieri off-road sia lunghi tratti di asfalto, è possibile con una gravel eBike. Ideale per viaggi avventurosi e perfettamente performanti anche in città, la gravel è agile, affidabile e confortevole.

With a gravel is possible to choose your own routes without planning team, tackle both off-road trails and log stretches of asphalt. Ideal for adventours trips and perfectly performing even in the city, the gravel is agile, reliable and comfortable.











-  Fazua Ev 2.0
-  Energy 250x
-  RMT
-  28"
-  11s
-  15,7 kg

Black / Red	
54	0116820800
58	0116820810

Frame	Alu, hydroformed, smooth welding, Flat mount disc brake, tapered, 12x142 mm
Fork	Carbon monocoque, Tapered, 12x100 mm, Flat mount disc brake
Headset	FSA No.57E tapered 1"1/2
Crankset	FSA CK-746, 40T
Rear Derailleur	Shimano GRX RD-R812, 11s
Shifters Levers	Shimano GRX ST-RX600 1x11s
Brakes	Shimano GRX BR-RX400, Rotor SM-RT64 160 mm/160 mm
Cassette	Shimano CS-M7000 11s 11/42
Wheels	Shimano WH-RS370
Stem	FSA ST-OS 97
Handlebar	FSA NS Adventure Compact
Seatpost	FSA Energy SBS
Saddle	Selle Royal Asphalt
Tyres	Schwalbe G-One Bite, 700x40"

Motor	Fazua 36V, 250W
Max Torque	55 Nm
Sensor Type	Torque
Battery	Fazua Energy 250x, weight 1,38 kg
Charger Type	2 A
Change Time	Up to 3,5 hours
Max Assisted Speed	25 km/h
Display	RMT
Power	Breeze: 75 % River: 150 % Rocket: 240 %



-  Fazua ride50
-  Energy 250x
-  RMT RX
-  28"
-  11s
-  15,7 kg

Black / Red	
54	0116820700

Frame	Alu, hydroformed, smooth welding, Flat mount disc brake, tapered, 12x142 mm
Fork	Carbon monocoque, Tapered, 12x100 mm, Flat mount disc brake
Headset	FSA No.57E tapered 1"1/2
Crankset	FSA CK-746, 40T
Rear Derailleur	Shimano GRX RD-R812, 11s
Shifters Levers	Shimano GRX ST-RX600 1x11s
Brakes	Shimano GRX BR-RX400, Rotor SM-RT64 160 mm/160 mm
Cassette	Shimano CS-M7000 11s 11/42
Wheels	Shimano WH-RS370
Stem	FSA ST-OS 97
Handlebar	FSA NS Adventure Compact
Seatpost	FSA Energy SBS
Saddle	Selle Royal Asphalt
Tyres	Schwalbe G-One Bite, 700x40"

Motor	Fazua 36V, 250W
Max Torque	55 Nm
Sensor Type	Torque
Battery	Fazua Energy 250x, weight 1,38 kg
Charger Type	2 A
Charge Time	Up to 3,5 hours
Max Assisted Speed	25 km/h
Display	RMT RX
Power	Breeze: 75 % River: 150 % Rocket: 240 %

E-Trekking

Stare a contatto con la natura, esplorare, scoprire, combinando il relax con l'esercizio fisico.

Solamente la tua eBike rende ogni viaggio più piacevole.

Being surrounded by nature, discover, explore, combining relax with exercise.

Your eBike makes every journey more pleasant.



ANZO agile







ANZO
powered by ANANDA
agile

ANZO
by ANANDA

easy





-  Bosch Perf. Line CX
-  PowerTube 625Wh
-  Kiox
-  29"
-  12s
-  26,6 kg







Man: Black/ Green

48

0116866510

Frame	Full Carbon 29", Toray T700, dual integrated battery, oversize head tube, 12x148 mm E-Thru	Motor	Bosch Performance Line CX 36 V, 250 W
Fork	Zoom 860S, Coil, Lockout, 29", Travel 100 mm, QR	Max Torque	85 Nm
Headset	Acros for Viper, 1,5", Internal routing	Sensor Type	Torque
Crankset	FSA 38T, Megatooth	Battery	PowerTube 625 Horizontal & predisposition for PowerTube 500 Horizontal
Rear Derailleur	Sram SX Eagle, 12s	Charger Type	4 A
Shifters Levers	Sram SX Eagle Single Click Trigger, 12s	Change Time	Up to 9 hours
Brakes	Shimano BR-MT200, Rotor SM-RT10 180 mm/180 mm	Max Assisted Speed	25 km/h
Cassette	Sram PG1210 Eagle 12s, 11/50	Display	Kiox
Pedals	Alu TKK	Power	Eco: 55 % Tour: 120 % EMTB: 200 % Turbo: 300 %
Front Hub	Shimano TX505, CL, 32h		
Rear Hub	Shimano TC500B, 12x148, CL, HG, 32h /Glory Wheel 12x148, CL, HG, 32h		
Rims	RADIALE X25, eDesign Asymmetric, Tubeless Ready, 622x25c		
Stem	Satori Viper0, 31,8 mm, Internal routing		
Handlebar	Alu, 720 mm, Barbore 31.8, Rise 25 mm		
Seatpost	Alu, 31,6 mm		
Saddle	Selle Royal Essenza		
Tyres	Vittoria Barzo, 29"x2,25"		
Mudguards	SKS A65R		
Chaincover	FSA Bash		
Carriers	Alu, without brackets		
External Lights	F: Herrmans MR GO - 120 lumen R: Axa BlueLine LED Lightguide		



-  Bosch Perf. CX Cruise
-  PowerTube 625Wh
-  Purion
-  29"
-  10s
-  26,5 kg

MAN: Black/ Green	
48	0116851915
52	0116851925







LADY: Black/ Green	
44	0116851900

Frame	Full Carbon 29", Toray T700, dual integrated battery, oversize head tube, 12x148 mm E-Thru
Fork	Zoom 860S, Travel 100 mm, Coil, Lockout
Headset	Acros for Viper, 1,5", Internal routing
Crankset	FSA 38T, Megatooth
Rear Derailleur	Shimano Deore RD-M5120, Shadow Plus
Shifters Levers	Shimano Deore SL-M4100 Rapidfire-Plus, 10s
Brakes	Shimano BR-MT200, Rotor SM-RT10 180 mm / 180 mm
Cassette	Shimano CS-M4100 10s 11/46
Pedals	Alu TKK
Front Hub	Shimano TC500B, 12x148, CL, HG, 32h
Rear Hub	Shimano Alivio MT400, 12x148, CL, HG, 32h / Glory Wheel 12x148, CL, HG, 32h
Rims	RADIALE X25, eDesign Asymmetric, Tubeless Ready, 622x25c
Stem	Satori Viper0, 31,8 mm, Internal routing
Handlebar	Alu Low Rise, 720 mm
Seatpost	Alu, 31,6 mm
Saddle	Atala Trekking
Tyres	Schwalbe Tough Tom K-Guard, 57-622

Motor	Performance CX 36 V, 250 W
Max Torque	85 Nm
Sensor Type	Torque
Battery	PowerTube 625 Horizontal & predisposition for PowerTube 500 Horizontal
Charger Type	4 A
Change Time	Up to 9,4 hours
Max Assisted Speed	25 km/h
Display	Purion
Power	Eco: 60 % Tour: 140 % EMTB: 140 / 340 % Turbo: 340 %











-  Bosch Perf. Line Smart System
-  PowerTube 625Wh
-  Intuvia + Led Remote
-  27,5"
-  10s
-  28,9 kg

Black	
45	0116871900
49	0116871910

Frame	Alu 29", Gravity casting, Easy Access, Integrated battery, Tapered, Internal routing, QR
Fork	Suntour XCM32-ATB, Coil, Lockout, 29" Travel 100 mm, QR
Headset	Acros AZF-585, 1.5", Internal routing
Crankset	FSA 38T
Rear Derailleur	Shimano CUES RD-U6000 GS Shadow, 10s
Shifters Levers	Shimano CUES SL-U6000 Rapidfire Plus, 10s
Brakes	Shimano BR-MT200, Rotor SM-RT10 180 mm/180 mm
Cassette	Shimano CUES CS-LG300, 10s, 11/48
Pedals	Alu TTK
Front Hub	Shimano TX505, CL, 32h
Rear Hub	Shimano TX505, CL, HG, 32h
Rims	Radiale E25, eBike Ready, Tubeless Ready, 584x25c
Stem	Satori Python, Barbore 31.8 mm, Adjustable, Internal routing
Handlebar	Alu, 640 mm, Barbore 31.8, Rise 25 mm, Back seep 25°
Seatpost	Satori Harmony, Suspended, 31.6 mm
Saddle	Selle Royal Vivo Unitec
Tyres	Schwalbe Hurricane Perf, RaceGuard, 27,5"x2.25"
Mudguards	SKS A65R
Chaincover	FSA Bash Guard
Carriers	Alu, without brackets, MIK
External Lights	F: Spanninga X&O 30 lux R: Axa Juno LED

Motor	Bosch Smart System Perf. Line 36 V, 250 W
Max Torque	75 Nm
Sensor Type	Torque
Battery	PowerTube 625 Horizontal, weight 3.5 kg
Charger Type	2 A
Change Time	Up to 9 hours
Max Assisted Speed	25 km/h
Display	Intuvia + Led Remote
Power	Eco: 60 % Tour: 140 % EMTB: 240 % Turbo: 340 %









-  Bosch Perf. Line Smart System
-  PowerTube 500Wh
-  Purion 200
-  27,5"
-  9s
-  28,3 kg

Black	
45	0116871950
49	0116871960

Frame	Alu 29", Gravity casting, Easy Access, Integrated battery, Tapered, Internal routing, QR
Fork	Suntour XCM32-ATB, Coil, Lockout, 29" Travel 100 mm, QR
Headset	Acros AZF-585, 1.5", Internal routing
Crankset	FSA 38T
Rear Derailleur	Shimano CUES RD-U4000 GS Shadow, 9s
Shifters Levers	Shimano CUES SL-U4000 Rapidfire Plus, 9s
Brakes	Shimano BR-MT200, Rotor SM-RT10 180 mm/180 mm
Cassette	Shimano CUES CS-LG300, 9s, 11/46
Pedals	Alu TTK
Front Hub	Shimano TX505, CL, 32h
Rear Hub	Shimano TX505, CL, HG, 32h
Rims	Radiale E25, eBike Ready, Tubeless Ready, 584x25c
Stem	Satori Python, Barbore 31.8 mm, Adjustable, Internal routing
Handlebar	Alu, 640 mm, Barbore 31.8, Rise 25 mm, Back seep 25°
Seatpost	Satori Harmony, Suspended, 31.6 mm
Saddle	Selle Royal Vivo Unitec
Tyres	Schwalbe Hurricane Perf, RaceGuard, 27,5"x2.25"
Mudguards	SKS A65R
Chaincover	FSA Bash Guard
Carriers	Alu, without brackets, MIK
External Lights	F: Spanninga X&O 30 lux R: Axa Juno LED

Motor	Bosch Smart System Perf. Line 36 V, 250 W
Max Torque	75 Nm
Sensor Type	Torque
Battery	PowerTube 500 Horizontal, weight 3.5 kg
Charger Type	2 A
Change Time	Up to 7 hours
Max Assisted Speed	25 km/h
Display	Purion 200
Power	Eco: 60 % Tour: 140 % EMTB: 240 % Turbo: 340 %









-  Bosch Performance CX
-  PowerTube 625Wh
-  Purion
-  29"
-  10s
-  24,8 kg

Blue/Brown	
46	0115307000
50	0115307010

Frame	Alu 29", Hydroformed, integrated battery, tapered, External routing, Forged interface, QR
Fork	Zoom 860 AMS, 100 mm, Coil, Lockout, QR
Headset	FSA No.57BP-1
Crankset	Miche 34T
Rear Derailleur	Shimano Deore RD-4120, Shadow Plus, 10s
Shifters Levers	Shimano Deore SL-M4100 Rapidfire-Plus, 10s
Brakes	Shimano BR-MT200, Rotor SM-RT30 180 mm / 180 mm
Cassette	Shimano CS-M1100 10s 11/46
Pedals	Alu MTB
Front Hub	Shimano TX505, CL, 36h
Rear Hub	Shimano TX505, CL, HG, 36h
Rims	RADIALE E25, eBike Ready, Tubeless Ready, 622x25c
Stem	Alu barbore, 31,8 mm
Handlebar	Alu, 720 mm, Barbore 31.8, Rise 25 mm
Seatpost	Alu, 31,6 mm
Saddle	Selle Royal Sauris
Tyres	Schwalbe Smart Sam, Performance, Addix, 29"x2,25" / Vittoria Barzo
Mudguards	SKS A65R
Chaincover	FSA Bash Guard
Carriers	Alu, without XLCets
External Lights	F: Herrmans Trelock VEO - 50 lumen R: Axa BlueLine LED Lightguide

Motor	Performance CX 36V, 250W
Max Torque	85 Nm
Sensor Type	Torque
Battery	PowerTube 625 Horizontal, frametype, weight 3,5 kg
Charger Type	4 A
Charge Time	Up to 5 hours
Max Assisted Speed	25 km/h
Display	Purion
Power	Eco: 60 % Tour: 140 % EMTB: 140 / 340% Turbo: 340 %









-  AM80
-  EnergyTube 540Wh
-  AM LCD FullColour
-  29"
-  12s
-  25,9 kg

Grey/Neon Red	
42	0116832555
46	0116832565
50	0116832575

Frame	Alu 29", Hydroformed, Integrated battery, Tapered, External routing, Forged interface, QR
Fork	Zoom 860 AMS, Coil, Lockout, 29", Travel 100 mm, QR
Headset	Acros for Viper, 1.5", Internal routing
Crankset	FSA, 34T, Megatooth
Rear Derailleur	Sram SX Eagle, 12s
Shifters Levers	Sram SX Eagle, 12s Single Click Trigger, 12s
Brakes	Shimano BR-MT200, Rotor SM-RT10 180 mm / 180 mm
Cassette	Sram PG1210 Eagle 12s, 11/50
Pedals	Alu MTB
Front Hub	Shimano TX505, CL, 32h
Rear Hub	Shimano TX505, CL, HG, 32h
Rims	RADIALE E25, eBike Ready, Tubeless Ready, 622x25c
Stem	Satori Viper0, 31,8 mm, Internal routing
Handlebar	Alu, 720 mm, Barbore 31.8, Rise 25 mm
Seatpost	Alu, 30,4 mm
Saddle	Selle Royal Sauris
Tyres	Schwalbe Smart Sam, Performance, Addix, 29"x2.35"
Mudguards	SKS A65R
Chaincover	FSA Bash Guard
Carriers	Alu, without brackets
External Lights	Front light on handlebar with battery Rear light on rear carrier with battery

Motor	AM-80 36 V, 250 W
Max Torque	80 Nm
Sensor Type	Torque
Battery	EnergyTube 540, frametype, weight 2,9 kg
Charger Type	2 A
Change Time	Up to 7 hours
Max Assisted Speed	25 km/h
Display	AM LCD ful-colour
Power	Mode 1: 50% Mode 2: 100% Mode 3: 200% Mode 4: 300% Mode 5: 400%









-  AM-80
-  EnergyTube 540Wh
-  AM LCD FullColour
-  29"
-  12s
-  25,9 kg

Grey/Neon Red	
42	0116832555
46	0116832565
50	0116832575

Frame	Alu 29", Hydroformed, Integrated battery, Tapered, External routing, Forged interface, QR
Fork	Zoom 860 AMS, Coil, Lockout, 29", Travel 100 mm, QR
Headset	Acros for Viper, 1.5", Internal routing
Crankset	FSA, 34T, Megatooth
Rear Derailleur	Sram SX Eagle, 12s
Shifters Levers	Sram SX Eagle, 12s Single Click Trigger, 12s
Brakes	Shimano BR-MT200, Rotor SM-RT10 180 mm / 180 mm
Cassette	Sram PG1210 Eagle 12s, 11/50
Pedals	Alu MTB
Front Hub	Shimano TX505, CL, 32h
Rear Hub	Shimano TX505, CL, HG, 32h
Rims	RADIALE E25, eBike Ready, Tubeless Ready, 622x25c
Stem	Satori Viper0, 31,8 mm, Internal routing
Handlebar	Alu, 720 mm, Barbore 31.8, Rise 25 mm
Seatpost	Alu, 30,4 mm
Saddle	Selle Royal Sauris
Tyres	Schwalbe Smart Sam, Performance, Addix, 29"x2.35"
Mudguards	SKS A65R
Chaincover	FSA Bash Guard
Carriers	Alu, without brackets
External Lights	Front light on handlebar with battery Rear light on rear carrier with battery

Motor	AM-80 36 V, 250 W
Max Torque	80 Nm
Sensor Type	Torque
Battery	EnergyTube 540, frametype, weight 2,9 kg
Charger Type	2 A
Change Time	Up to 7 hours
Max Assisted Speed	25 km/h
Display	AM LCD ful-colour
Power	Mode 1: 50% Mode 2: 100% Mode 3: 200% Mode 4: 300% Mode 5: 400%



-  Bosch Perf. Line Smart System
-  PowerTube 750Wh
-  Kiox 300 + Led Remote
-  28"
-  12s
-  29,2 kg

MAN: Brown/ Silver	
49	0115326400
53	0115326410
59	0115326420







LADY: Anthracite/ Black	
45	0115326450
49	0115326460
53	0115326470

Frame	Alu, 700C, Gravity casting, Integrated battery, Tapered, Internal routing, QR
Fork	Suntour NVX30, Coil, Lockout, 29", Travel 63 mm, QR / Zoom 187D - 188D
Headset	Acros for Phyotn, 1,5", Internal routing
Crankset	FSA, 38T, MegaTooth
Rear Derailleur	Shimano XT RD-M8100 SGS Shadow Plus, 12s
Shifters Levers	Shimano Deore SL-M6100 Rapidfire-Plus, 12s
Brakes	Shimano BR-MT200, Rotor SM-RT10 180mm/180mm
Cassette	Shimano CS-M6100, 12s, 10/51
Pedals	Alu TTK
Front Hub	Shimano TX505, CL, 32h
Rear Hub	Shimano MT401, CL, MS, 32h
Rims	Radiale E25, eBike Ready, Tubeless Ready, 622x25c
Stem	Satori Python, Barbore 31.8 mm, Adjustable, Internal routing
Handlebar	Satori Noirette City, 630 mm, Barbore 31.8 mm, Rise 21 mm, Back sweep 30°
Seatpost	Satori Harmony, Suspended, 31,6 mm
Saddle	Atala Memory Foam Trekking
Tyres	Schwalbe Energizer Active Plus, Greenguard, TwinSkin, 700x55 / Vittoria Randoneur
Mudguards	SKS A65
Chaincover	SKS Chainbow
Carriers	Alu, without brackets
External lights	F: Spanninga X&O30 - 30 lux R: Axa Juno LED Lightguide

Motor	Bosch Smart System Perf. Line 36 V, 250W
Max Torque	75 Nm
Sensor Type	Torque
Battery	PowerTube 750 Horizontal, weight 4,2 kg
Charger Type	2 A
Change Time	Up to 9 hours
Max Assisted Speed	25 km/h
Display	Kiox 300 + Led Remote
Power	Eco: 60 % Tour: 140 % Auto: Adaptive max 340 % Turbo: 340 %





-  Bosch Perf. Line
-  PowerTube 625Wh
-  Purion
-  28"
-  10s
-  27,4 kg







LADY: Blue/ Anthracite	
45	0115307800
50	0115307810
53	0115307820
MAN: Black/ Anthracite	
50	0115307700
53	0115307710
59	0115307720

Frame	Alu, 700C, Hydroformed, Integrated battery, Tapered, Internal routing, QR
Fork	Suntour NVX30, Coil, Lockout, 29", Travel 63 mm, QR / Zoom 187D - 188D
Headset	Acros for Phyotn, 1,5", Internal routing
Crankset	FSA 38T
Rear Derailleur	Shimano Deore RD-M5120, Shadow Plus
Shifters Levers	Shimano Deore SL-M4100 Rapidfire-Plus, 10s
Brakes	Shimano BR-MT200, Rotor SM-RT10 180mm/180mm
Cassette	Shimano CS-M4100 10s 11/46
Pedals	Alu TKK
Front Hub	Shimano TX505, CL, 32h
Rear Hub	Shimano TX505, CL, HG, 32h
Rims	RADIALE E25, eBike Ready, Tubeless Ready, 622x25c
Stem	Satori Python, Barbore 31.8 mm, Adjustable, Internal routing
Handlebar	Satori Noirette City, 630 mm, Barbore 31.8 mm, Rise 21 mm, Back sweep 30°
Seatpost	Satori Harmony, Suspended, 31,6 mm
Saddle	Atala Memory Foam Trekking
Tyres	Schwalbe Energizer Active Plus, Greenguard, TwinSkin, 700x55 / Vittoria Randoneur
Mudguards	SKS A65
Chaincover	SKS Chaibow
Carriers	Alu, without brackets
External Lights	F: Herrmans MR GO - 120 lumen R: Axa BlueLine LED Lightguide

Motor	Bosch Perf. Line 36 V, 250W
Max Torque	65 Nm
Sensor Type	Torque
Battery	PowerTube 625 Horizontal, type, weight 3,5 kg
Charger Type	2 A
Change Time	Up to 9 hours
Max Assisted Speed	25 km/h
Display	Purion
Power	Eco: 55 % Tour: 120 % Sport: 200 % Turbo: 300 %





-  Bosch Perf. Cruise
-  PowerTube 500Wh
-  Purion
-  28"
-  9s
-  26,8 kg







MAN: Grey/ Blue	
50	0115296906
53	011296916
LADY: Anthracite/ Green	
45	0115297006

Frame	Alu, 700C, Hydroformed, Integrated battery, Tapered, Internal routing, QR
Fork	Suntour NEX-E25, Coil, Lockout, 28", Travel 63 mm, QR / Zoom 187D - 188D
Headset	Acros for Phytotn, 1,5", Internal routing
Crankset	FSA 38T
Rear Derailleur	Sram Rear Derailleur, X5 9s
Shifters Levers	Sram Shifter Lever X5 Multiple click, 9s
Brakes	Shimano BR-MT200, Rotor SM-RT10 180 mm / 180 mm
Cassette	Sram Cassette PG-920, 9s, 11/34
Pedals	Alu TTK
Front Hub	Shimano TX505, CL, 32h
Rear Hub	Shimano TX505, CL, HG, 32h
Rims	Radiale E25, eBike Ready, Tubeless Ready, 622x25c
Stem	Satori Python, Barbore 31.8 mm, Adjustable, Internal routing
Handlebar	Satori Noirette City, 630 mm, Barbore 31.8 mm, Rise 21 mm, Back sweep 30°
Seatpost	Satori Harmony, Suspended, 31.6 mm
Saddle	Atala Memory Foam Trekking
Tyres	Schwalbe Energizer Active Plus, Greenguard, TwinSkin, 700x50c / Vittoria Randoneur
Mudguards	SKS A60S
Chaincover	SKS Chainbow
Carriers	Racktime Eco2.0 - Imm System
External Lights	F: Herrmans MR GO - 120 lumen R: Axa BlueLine LED Lightguide

Motor	Performance Cruise 36 V, 250W
Max Torque	65 Nm
Sensor Type	Torque
Battery	PowerTube 500 Horizontal, frametype, weight 2,8kg
Charger Type	2 A
Change Time	Up to 7,5 hours
Max Assisted Speed	25 km/h
Display	Purion
Power	Eco: 55 % Tour: 120 % Sport: 200 % Turbo: 300 %











-  Bosch Perf. Line
-  PowerTube 500Wh
-  Purion
-  28"
-  9s
-  26,8 kg

Silver	
45	0115328700

Frame	Alu, 700C, Hydroformed, Integrated battery, Tapered, Internal routing, QR
Fork	Zoom 187D AMS, Coil, 28", Travel 65 mm, QR
Headset	Acros for Phyotn, 1,5", Internal routing
Cranckset	Miranda 38T
Rear Derailleur	Sram Rear Derailleur, X5 9s
Shifters Levers	Sram Shifter Lever X5 Multiple click, 9s
Brakes	Shimano BR-MT200, Rotor SM-RT10 180 mm / 180 mm
Cassette	Sram Cassette PG-920, 9s, 11/34
Pedals	Alu TTK
Front Hub	Shimano TX505, CL, 32h
Rear Hub	Shimano TX505, CL, HG, 32h
Rims	Rodi Viper 28, 622x23
Stem	Satori Python, Barbore 31.8 mm, Adjustable, Internal routing
Handlebar	Satori Noirette City, 630 mm, Barbore 31.8 mm, Rise 21 mm, Back sweep 30°
Seatpost	Satori Harmony, Suspended, 31.6 mm
Saddle	Sella Italia, Modelx SuperFlow Comfort
Tyres	Continental, Contact Cruiser, Black reflex, 55-622
Mudguards	SKS A60S
Chaincover	SKS Chainbow
Carriers	Racktime Eco2.0 - Imm System
External Lights	F: Herrmans MR GO - 120 lumen R: Axa BlueLine LED Lightguide

Motor	Bosch Perf. Line 36 V, 250W
Max Torque	65 Nm
Sensor Type	Torque
Battery	PowerTube 500 Horizontal, frametype, weight 2,8kg
Charger Type	2 A
Change Time	Up to 7,5 hours
Max Assisted Speed	25 km/h
Display	Purion
Power	Eco: 55 % Tour: 120 % Sport: 200 % Turbo: 300 %



-  Bosch Active Plus
-  Powerpack 500Wh
-  Purion
-  28"
-  9s
-  26,2 kg

MAN: Satin Grey	
50	0115307906







LADY: Brown/ Anthracite	
45	0115308006

Frame	Alu, 700C, Hydroformed, Internal PowerPack battery, Tapered, Internal routing, QR
Fork	Zoom 187D AMS, Coil, 28", Travel 65 mm, QR
Headset	Acros for Phyotn, 1,5", Internal routing
Cranckset	Miranda 38T
Rear Derailleur	Sram Rear Derailleur, X5 9s
Shifters Levers	Sram Shifter Lever X5 Multiple click, 9s
Brakes	Shimano BR-MT200, Rotor SM-RT10 180 mm / 180 mm
Cassette	Sram Cassette PG-920, 9s, 11/34
Pedals	Alu TTK
Front Hub	Shimano TX505, CL, 32h
Rear Hub	Shimano TX505, CL, HG, 32h
Rims	RADIALE E25, eBike Ready, Tubeless Ready, 622x25c
Stem	Satori Python, 31,8 mm, Adjustable, Internal routing
Handlebar	Satori Noirette City, 630 mm, Barbore 31.8 mm, Rise 21 mm, Back sweep 30°
Seatpost	Satori Harmony, Suspended, 30,9 mm
Saddle	Atala Memory Foam Trekking
Tyres	Schwalbe Energizer Active Plus, Punctureguard, TwinSkin, 700x50C / Victoria Randonneur
Mudguards	SKS A60S
Chaincover	SKS Chainbow
Carriers	Alu, without brackets
External Lights	F: Herrmans MR GO - 120 lumen R: Axa BlueLine LED Lightguide

Motor	Bosch Active Plus 36V, 250W
Max Torque	50 Nm
Sensor Type	Torque
Battery	Powerpack 500 Horizontal, frametype, weight 2,6kg
Charger Type	2 A
Change Time	Up to 6,5 hours
Max Assisted Speed	25 km/h
Display	Purion
Power	Eco: 55 % Tour: 120 % Sport: 200 % Turbo: 300 %





-  Bosch Active Plus
-  Powerpack 400Wh
-  Purion
-  28"
-  9s
-  25,9 kg

MAN: Green/ Anthracite	
50	0115297306
53	0115297316







LADY: White/ Grey	
45	0115297406
50	0115297416

Frame	Alu, 700C, Hydroformed, Internal PowerPack battery, Tapered, Internal routing, QR
Fork	Suntour NEX, Coil, Travel 63 mm, QR / Zoom 187D - 188D
Headset	Acros for Phyotn, 1,5", Internal routing
Cranckset	Miranda 38T
Rear Derailleur	Sram Rear Derailleur, X5 9s
Shifters Levers	Sram Shifter Lever X5 Multiple click, 9s
Brakes	Shimano BR-MT200, Rotor SM-RT10 180 mm / 180 mm
Cassette	Sram Cassette PG-920, 9s, 11/34
Pedals	Alu TTK
Front Hub	Shimano TX505, CL, 32h
Rear Hub	Shimano TX505, CL, HG, 32h
Rims	RADIALE E25, eBike Ready, Tubeless Ready, 622x25c
Stem	Satori Python, 31,8 mm, Adjustable, Internal routing
Handlebar	Satori Noirette City, 630 mm, Barbore 31.8 mm, Rise 21 mm, Back sweep 30°
Seatpost	Satori Harmony, Suspended, 30,9 mm
Saddle	Atala Memory Foam Trekking
Tyres	Schwalbe Energizer Active Plus, Punctureguard, TwinSkin, 700x50C / Victoria Randonneur
Mudguards	SKS A60S
Chaincover	SKS Chainbow
Carriers	Alu, without brackets
External Lights	F: Herrmans MR GO - 120 lumen R: Axa BlueLine LED Lightguide

Motor	Active Plus 36V, 250W
Max Torque	50 Nm
Sensor Type	Torque
Battery	Powerpack 400 Horizontal, frametype, weight 2,5kg
Charger Type	2 A
Charge Time	Up to 7,5 hours
Max Assisted Speed	25 km/h
Display	Purion
Power	Eco: 55 % Tour: 120 % Sport: 200 % Turbo: 300 %





-  Bosch Active
-  Powerpack 400Wh
-  Purion
-  28"
-  7s
-  25,6 kg

MAN: Anthracite/ Black	
50	0115297504
53	0115297514







LADY: Green/ Anthracite	
45	0115297604
50	0115297614

Frame	Alu, 700C, Hydroformed, Internal PowerPack battery, Tapered, Internal routing, QR
Fork	Suntour NEX, Coil, Travel 63 mm, QR / Zoom 187D - 188D
Headset	Acros universal, 1,5", Internal routing
Crankset	Miranda 38T
Rear Derailleur	LT, RD-V4007-M-2, 7s
Shifters Levers	LT, SL-V4007-7W-2, 7s
Brakes	Shimano BR-MT200, Rotor SM-RT10 180 mm / 180 mm
Cassette	LT, FW-207, 7s, 13-28T
Pedals	Alu TTK
Front Hub	Shimano TX505, CL, 32h
Rear Hub	Chosen, CL, FW 7s, 32h
Rims	Radiale E25, eBike Ready, Tubeless Ready, 622x25c
Stem	Alu, Barbore 31.8 mm, Adjustable
Handlebar	Alu, 640 mm, Barbore 31.8 mm, Rise 25 mm, Back sweep 25°
Seatpost	Alu, 30,9 mm
Saddle	Atala Memory Foam Trekking
Tyres	Schwalbe Energizer Active Plus, Punctureguard, TwinSkin, 700x50C / Victoria Randonneur
Mudguards	SKS A60S
Chaincover	SKS Chainbow
Carriers	Alu, without brackets
External Lights	F: Herrmans MR GO - 120 lumen R: Axa BlueLine LED Lightguide

Motor	Bosch Active 36 V, 250W
Max Torque	40 Nm
Sensor Type	Torque
Battery	Powerpack 400Wh, frametype, weight 2,5kg
Charger Type	2 A
Change Time	Up to 6,5 hours
Max Assisted Speed	25 km/h
Display	Purion
Power	Eco: 40 % Tour: 100 % Sport: 180 % Turbo: 250 %





-  Agile Gen2
-  Phylion 603Wh
-  Atala A10 LCD CAN
-  28"
-  9s
-  28,5kg

MAN: Blue Navy	
49	0115310500







LADY: Green Forest	
45	0115310600

Frame	Alu. Hydroformed 700c, internal battery, internal cables
Fork	Suntour NVX30 NLO 700c, alu with alu crown, 63mm travel, 30mm stanchions, with hydraulic lockout
Headset	FSA integrated ahead 1"1/8
Crankset	Alu 170mm, FSA 38T
Rear Derailleur	Shimano Alivio RD-M3100
Shifters Levers	Shimano Alivio SL-M3100, 9s
Brakes	Shimano BR-MT200 hydraulic disc, Rotor 180 mm CL
Cassette	Shimano HG200 9s 11/36
Pedals	Alu Comfort
Hub	Shimano TX505, CL, 32h, quick release
Rims	Radiale E25 700c, double wall, 32h, disc
Stem	Au over, ahead, adjustable
Handlebar	Alu over TKK, 640mm, rise 25mm
Seatpost	Suspended 40mm, 30,9mm
Saddle	Selle Royal Lancia
Tyres	Schwalbe Energizer Plus 700x55c, with reflecting line, puncture proof
Mudguards	Single stay speedy, edge
Chaincover	L type, edge
Carriers	Rear alu 14mm with spring, 25kg load
External Lights	Axa front (30 lux) and rear LED, controlled by display and twilight sensor

Motor	Agile Gen2 CAN 36 V, 250W
Max Torque	100 Nm
Sensor Type	Torque
Battery	Phylion Li-Ion 36V, 603Wh, inside frame, with Smart BMS CAN
Charger Type	2 A Europlug
Change Time	100%: 8h:52m / 80%: 6h42m
Max Assisted Speed	25 km/h
Display	Atala A10 LCD CAN, glass/metal with remote control
Power	5 levels, Power adjust level1: 50% level2: 100% level3: 150% level4: 200% level5: 250%
Other Functions	Walking assistance External light control Speed information Battery information





-  Agile Gen2
-  Phyllion 522Wh
-  Atala A10 LCD CAN
-  28"
-  8s
-  28,3 kg

MAN: Anthracite	
49	0115310700
54	0115310750







LADY: Ultralight	
45	0115310800

Frame	Alu. Hydroformed 700c, internal battery, internal cables
Fork	HL CH-187 HLO 700c, alu with alu crown, 65mm travel, 30mm stanchions
Headset	FSA integrated ahead 1"1/8
Crankset	Alu 170mm, FSA 38T
Rear Derailleur	Shimano Acera RD-M3020
Shifters Levers	Shimano SL-M315 PushPull, 8s
Brakes	Shimano BR-MT200 hydraulic disc, Rotor 180 mm CL
Cassette	Shimano HG200 8s 12/32
Pedals	Alu Comfort
Hub	Shimano TX505, CL, 32h, quick release
Rims	Radiale E25 700c, double wall, 32h, disc
Stem	Au over, ahead, adjustable
Handlebar	Alu over TKK, 640mm, rise 25mm
Seatpost	Suspended 40mm, 30,9mm
Saddle	Selle Royal Lancia
Tyres	Schwalbe Road Cruiser 700x47c, with reflecting line, puncture proof
Mudguards	Single stay speedy, edge
Chaincover	L type, edge
Carriers	Rear alu 14mm with spring, 25kg load
External Lights	Axa front (30 lux) and rear LED, controlled by display and twilight sensor

Motor	Agile Gen2 CAN 36 V, 250W
Max Torque	100 Nm
Sensor Type	Torque
Battery	Phyllion Li-Ion 36V, 522Wh, inside frame, with Smart BMS CAN
Charger Type	2 A Europlug
Change Time	100%: 7h:45m / 80%: 5h48m
Max Assisted Speed	25 km/h
Display	Atala A10 LCD CAN, glass/metal with remote control
Power	5 levels, Power adjust level1: 50% level2: 100% level3: 150% level4: 200% level5: 250%
Other Functions	Walking assistance External light control Speed information Battery information





-  Agile Gen2
-  Phylion 522Wh
-  Atala A10 LCD Smart
-  28"
-  7s
-  28,3 kg

MAN: Blu Navy	
49	0115310900
54	0115310950







LADY: Green Forest	
45	0115311000
49	0115311050

Frame	Alu. Hydroformed 700c, integrated battery, internal cables
Fork	Suntour NEX 700c, alu with alu crown, 63mm travel
Headset	FSA integrated 1"1/8
Crankset	Alu 170mm, Miche 38T
Rear Derailleur	Shimano Altus RD-M310
Shifters Levers	Shimano SL-M315 PushPull, 7s
Brakes	Shimano BR-MT200 hydraulic disc, Rotor 180 mm CL
Cassette	Shimano HG200 8s 12/32
Pedals	Resin antislip
Hub	Shimano TX505, CL, 32h, quick release
Rims	Radiale E25 700c, double wall, 32h, disc
Stem	Alu over, ahead, adjustable
Handlebar	Alu over TKK, 640mm, rise 25mm
Seatpost	Byte suspended 40mm, 25mm
Saddle	Selle Royal Lancia
Tyres	Byte Trento 700x45c, with reflecting line
Mudguards	Single stay speedy
Chaincover	L type, edge
Carriers	Rear alu 14mm with spring, 25kg load
External Lights	Axa front (15 lux) and rear LED, controlled by display

Motor	Agile Gen2 CAN 36 V, 250W
Max Torque	100 Nm
Sensor Type	Torque
Battery	Phylion Li-Ion 36V, 522Wh, on frame, with Smart BMS CAN
Charger Type	2 A Europlug
Change Time	100%: 7h:45m / 80%: 5h48m
Max Assisted Speed	25 km/h
Display	Atala A23 LCD CAN, side
Power	5 levels, Power adjust level1: 50% level2: 100% level3: 150% level4: 200% level5: 250%
Other Functions	Walking assistance External light control Speed information Power information Battery information





-  Agile Can
-  Phylion 418Wh
-  Atala A15 LED CAN
-  28"
-  7s
-  28,2 kg

**MAN LT: Anthracite/
Red**

49 0115309402

**LADY: Blue/ Pastel
Grey**







45 0115309500

Frame	Alu. Hydroformed 700c, integrated battery, internal cables
Fork	Suntour NEX 700c, alu with alu crown, 50mm
Headset	FSA integrated 1"1/8
Crankset	AM80 alu 170mm, FSA 38T
Rear Derailleur	Shimano Altus RD-M310 / L-TWOO RD-V4007-M-2, 7s
Shifters Levers	Shimano SL-M315 PushPull, 7s / L-TWOO SL-V4007-7W-2, 7s
Brakes	Shimano BR-MT200 hydraulic disc, Rotor 160 mm CL
Cassette / Freewheel	Shimano HG200 7s 12/32 / L-TWOO FW-207 7s 13-28
Pedals	Resin antislip
Hub	Shimano TX505, Cl, 32h, quick release / Shimano TX505/Alu filetto 32h, CL, quick release
Rims	Rodi 700c, double wall w/eylets, 32h, disc
Stem	Byte alu, ahead, adjustable
Handlebar	Byte steel TKK
Seatpost	Byte alu with clamp, 27,2mm
Saddle	Selle Royal Lancia
Tyres	Byte Trento 700x45c, with reflecting line
Mudguards	Single stay speedy
Chaincover	Plastic, L type
Carriers	Rear alu 14mm with spring, 25kg load
External Lights	Axa front (30 lux) and rear LED, controlled by display

Motor	AM80 Agile CAN 36 V, 250W
Max Torque	80 Nm
Sensor Type	Torque
Battery	Phylion Li-Ion 36V, 418Wh, on frame, with Smart BMS CAN
Charger Type	2 A Europlug
Change Time	100%: 6h:30m / 80%: 4h40m
Max Assisted Speed	25 km/h
Display	Atala A15 LED CAN, Power +/-
Power	5 levels, Power adjust level1: 50% level2: 100% level3: 150% level4: 200% level5: 250%
Other Functions	Walking assistance External light control





-  AM80 Easy
-  Phylion 418Wh
-  Atala A19 Digit LED UART
-  28"
-  7s
-  24,5 kg

MAN: Anthracite	
49	0115311100

LADY: Ultralight	
45	0115311200

Frame	Alu. Hydroformed 700c, integrated battery, internal cables
Fork	HL CH-187 700c, alu with alu crown, 65mm travel, 30mm stanchions
Headset	FSA integrated ahead 1"1/8
Crankset	Alu 170mm, Miche 38T
Rear Derailleur	Shimano Tourney RD-TY500
Shifters Levers	Shimano SL-M315 PushPull, 7s
Brakes	Shimano BR-MT200 hydraulic disc, Rotor 160 mm CL
Cassette	Shimano HG200 7s 12-32
Pedals	Resin antislip
Hub	Shimano TX505, CL, 32h, quick release
Rims	Rodi 700c, double wall w/eylets, 32h, disc
Stem	Byte alu, ahead, adjustable
Handlebar	Byte alu TKK, 630mm, rise 30mm
Seatpost	Byte alu with clamp, 27,2mm
Saddle	Selle Royal Shadow
Tyres	Byte Trento 700x45c, with reflecting line
Mudguards	Single stay speedy, edge
Chaincover	L type, edge
Carriers	Rear steel 10mm with spring, no bracket, 25kg load
External Lights	Axa front (15 lux) and rear LED, controlled by display

Motor	AM80 Easy UART 36 V, 250W
Max Torque	70 Nm
Sensor Type	Torque
Battery	Phylion Li-Ion 36V, 418Wh, on frame, with Smart BMS UART
Charger Type	2 A Europlug
Change Time	100%: 6h:18m / 80%: 4h38m
Max Assisted Speed	25 km/h
Display	Atala A19 Digit LED UART
Power	5 levels, Power adjust level1: 50% level2: 100% level3: 150% level4: 200% level5: 250%
Other Functions	Walking assistance External light control Speed information Battery range %









E-Urban

Spostarsi velocemente in città è sempre più difficile: strade intasate, metro affollatissime, treni in ritardo fanno ormai parte del passato. L'eBike ti permette questo e molto altro, diventando parte integrante della mobilità urbana.

Moving quickly in the city is more and more difficult: congested streets, stuffy subways, train delays. Not any more. The eBike makes commuting easier, becoming an essential part of urban mobility.











-  Bosch Perf. Line
-  PowerTube 500Wh
-  Purion
-  28"
-  9s
-  27,6 kg

Blue	
45	0115328650

Frame	Alu, 700C, Hydroformed, Easy access, Integrated battery, Tapered, Internal routing, QR
Fork	Suntour NEX, 63 mm, QR
Headset	Acros for Phyotn, 1,5", Internal routing
Crankset	Miranda 38T
Rear Derailleur	Sram Rear Derailleur, X5 9s
Shifters Levers	Sram Shifter Lever X5 Multiple click, 9s
Brakes	Shimano BR-MT200, Rotor Clarks 180 mm/180 mm
Cassette	Sram Cassette PG-920, 9s, 11/34
Pedals	Alu TKK
Front Hub	Chosen, QR, 36h
Rear Hub	Shimano TX505, CL, HG, 32h
Rims	Rodi Viper 28, 622x23
Stem	Satori Python, 31,8 mm, Adjustable, Internal routing
Handlebar	Satori Noirette City, 630 mm, Barbore 31.8 mm, Rise 21 mm, Back sweep 30°
Seatpost	Alu, 31,6 mm
Saddle	Sella Italia, Modelx SuperFlow Comfort
Tyres	Continental, Contact Cruiser, Black reflex, 55-622
Mudguards	SKS A60S
Chaincover	SKS Chainbow
Carriers	Racktime Eco2.0 - Imm system
External Lights	F: Axa Compact line R: Axa BlueLine LED Lightguide

Motor	Bosch Perf. Line 36 V, 250W
Max Torque	65 Nm
Sensor Type	Torque
Battery	PowerTube 500 Horizontal, weight 2,9kg
Charger Type	2 A
Change Time	Up to 7,5 hours
Max Assisted Speed	25 km/h
Display	Purion
Power	Eco: 55 % Tour: 120 % Sport: 200 % Turbo: 300 %









-  Bosch Active Plus
-  PowerTube 500Wh
-  Purion
-  28"
-  9s
-  27,3 kg

Blue	
45	0115328300
50	0115328310

Frame	Alu, 700C, Hydroformed, Easy access, Integrated battery, Tapered, Internal routing, QR
Fork	Zoom 187D AMS, Coil, 28", Travel 65 mm, QR
Headset	Acros for Phyotn, 1,5", Internal routing
Crankset	Miranda 38T
Rear Derailleur	Sram Rear Derailleur, X5 9s
Shifters Levers	Sram Shifter Lever X5 Multiple click, 9s
Brakes	Shimano BR-MT200, Rotor Clarks 180 mm/180 mm
Cassette	Sram Cassette PG-920, 9s, 11/34
Pedals	Alu TKK
Front Hub	Shimano TX505, CL, 32h
Rear Hub	Shimano TX505, CL, HG, 32h
Rims	Rodi Viper 28, 622x23
Stem	Satori Python, 31,8 mm, Adjustable, Internal routing
Handlebar	Satori Noirette City, 630 mm, Barbore 31.8 mm, Rise 21 mm, Back sweep 30°
Seatpost	Alu, 31,6 mm
Saddle	Sella Italia, Modelx SuperFlow Comfort
Tyres	Continental, Contact Cruiser, Black reflex, 55-622
Mudguards	SKS A60S
Chaincover	SKS Chainbow
Carriers	Racktime Eco2.0 - Imm system
External Lights	F: Axa Compact line R: Axa BlueLine LED Lightguide

Motor	Bosch Active Plus 36 V, 250W
Max Torque	50 Nm
Sensor Type	Torque
Battery	PowerTube 500 Horizontal, weight 2,9kg
Charger Type	2 A
Change Time	Up to 7,5 hours
Max Assisted Speed	25 km/h
Display	Purion
Power	Eco: 55 % Tour: 120 % Sport: 200 % Turbo: 300 %









-  Bosch Active Plus
-  Powerpack 500Wh
-  Intuvia
-  28"
-  9s
-  26,7 kg

Black/ Gray	
45	0115297908
50	0115297918

Frame	Alu, 700C, Hydroformed, Easy access, Internal PowerPack battery, Tapered, Internal routing, QR
Fork	Suntour NEX, Coil, Travel 63 mm, QR / Zoom 187D - 188D
Headset	Acros for Phyotn, 1,5", Internal routing
Cranckset	Miranda 38T
Rear Derailleur	Shimano Altus RD-M2000 SGS, Shadow
Shifters Levers	Shimano Altus SL-M2010 Rapidfire, 9s
Brakes	Shimano BR-MT200, Rotor SM-RT10 180 mm / 180 mm
Cassette	Shimano CS-HG200 9s 11/36
Pedals	Alu TTK
Front Hub	Shimano TX505, CL, 32h
Rear Hub	Shimano TX505, CL, HG, 32h
Rims	Radiale E25, eBike Ready, Tubeless Ready, 622x25c
Stem	Satori Python, Barbore 31.8 mm, Adjustable, Internal routing
Handlebar	Satori Noirette City, 630 mm, Barbore 31.8 mm, Rise 21 mm, Back sweep 30°
Seatpost	Alu, 31,6 mm
Saddle	Atala Memory Foam City
Tyres	Schwalbe Energizer Active Plus, Punctureguard, TwinSkin, 700x50C
Mudguards	SKS A60S
Chaincover	SKS Chainbow
Carriers	Racktime Eco2.0 - Imm system
External lights	F: Herrmans MR GO - 120 lumen R: Axa BlueLine LED Lightguide

Motor	Bosch Active Plus 36 V, 250W
Max Torque	50 Nm
Sensor Type	Torque
Battery	Powerpack 500Wh, frametype, weight 2,6kg
Charger Type	2 A
Change Time	Up to 7,5 hours
Max Assisted Speed	25 km/h
Display	Intuvia
Power	Eco: 55 % Tour: 120 % Sport: 200 % Turbo: 300 %

-  Bosch Active Plus
-  Powerpack 400Wh
-  Purion
-  28"
-  7s
-  26,7 kg









Blu	
45	0115300100

Frame	Alu, 700C, Hydroformed, Easy access, Internal PowerPack battery, Tapered, Internal routing, QR
Fork	Zoom 187D AMS, Coil, 28", Travel 65 mm, QR
Headset	Acros for Phytotn, 1,5", Internal routing
Crankset	Miranda 38T
Rear Derailleur	LT, RD-V4007-M-2, 7s
Shifters Levers	LT, SL-V4007-7W-2, 7s
Brakes	Shimano BR-MT200, Rotor SM-RT10 180 mm / 180 mm
Cassette	LT, FW-207, 7s, 13-28T
Pedals	Alu TTK
Front Hub	Shimano TX505, CL, 32h
Rear Hub	Chosen, CL, FW 7s, 32h
Rims	Rodi Viper 28, 622x23
Stem	Satori Python, Barbore 31.8 mm, Adjustable, Internal routing
Handlebar	Satori Noirette City, 630 mm, Barbore 31.8 mm, Rise 21 mm, Back sweep 30°
Seatpost	Alu, 30,9 mm
Saddle	Sella Italia, Modelx SuperFlow Comfort
Tyres	Schwalbe Energizer Active Plus, Punctureguard, TwinSkin, 700x50C / Victoria Randonneur
Mudguards	SKS A60S
Chaincover	SKS Chainbow
Carriers	Alu, without brackets
External Lights	F: Herrmans MR GO - 120 lumen R: Axa BlueLine LED Lightguide

Motor	Bosch Active Plus 36V, 250W
Max Torque	50 Nm
Sensor Type	Torque
Battery	Powerpack 400Wh, frametype, weight 2,5kg
Charger Type	2 A
Change Time	Up to 6,5 hours
Max Assisted Speed	25 km/h
Display	Purion
Power	Eco: 55 % Tour: 120 % Sport: 200 % Turbo: 300 %









-  Bosch Active Plus
-  Powerpack 400Wh
-  Purion
-  28"
-  9s
-  25,4 kg

White/ Red	
47	0115298007
50	0115298017
53	0115298027

Frame	Alu 700C, hydroformed, easy access, custom tubing, Internal routing, Forged interface / QR
Fork	Suntour NEX-E25, 63 mm, Coil
Headset	Acros AZF-585, 1,5", Internal routing
Crankset	Miranda 38T
Rear Derailleur	LT, RD-V54009-L2, 9s
Shifters Levers	LT, SL-V54009-9W, 9s
Brakes	Clarks M2, Rotor 180mm/180mm
Cassette	LT, CS-A5, 9s, 11-34T
Pedals	Alu TKK
Front Hub	Shimano TX505, CL, 32h
Rear Hub	Shimano TX505, CL, HG, 32h
Rims	RADIALE E25, eBike Ready, Tubeless Ready, 622x25c
Stem	Satori Python, 31,8 mm, Adjustable, Internal routing
Handlebar	Satori Noirette City, 630 mm
Seatpost	Alu, 30,9 mm
Saddle	Atala Memory Foam City
Tyres	Schwalbe Energizer Active Plus, Punctureguard, TwinSkin, 700x50C
Mudguards	SKS A60S
Chaincover	SKS Chainbow
Carriers	Alu, without brackets
External Lights	F: Herrmans MR GO - 120 lumen R: Axa BlueLine LED Lightguide

Motor	Bosch Active Plus 36V, 250W
Max Torque	50 Nm
Sensor Type	Torque
Battery	Powerpack 400Wh, frametype, weight 2,5kg
Charger Type	2 A
Change Time	Up to 6,5 hours
Max Assisted Speed	25 km/h
Display	Purion
Power	Eco: 55 % Tour: 120 % Sport: 200 % Turbo: 300 %









-  Bosch active Plus
-  Powerpack 400Wh
-  Purion
-  28"
-  8s
-  25,4 kg

Green	
45	0115328600

Frame	Alu, 700C, Hydroformed, Easy access, Integrated battery, Tapered, Internal routing, QR
Fork	Zoom 187D AMS, Coil, 28", Travel 65 mm, QR
Headset	FSA No.10 1"1/8
Crankset	Miranda 38T
Rear Derailleur	Shimano RD-M3020, 8s
Shifters Levers	Shimano Tourney SL-RV400 RevoShift, 8s
Brakes	Shimano BR-MT200, Rotor 160 mm/160mm
Cassette	Shimano CS-HG200, 8s, 12/32
Pedals	Alu TKK
Front Hub	Chosen, QR, 36h
Rear Hub	Shimano TX505, CL, HG, 32h
Rims	Rodi Viper 28, 622x23
Stem	Satori Python, 31,8 mm, Adjustable, Internal routing
Handlebar	Alu, 640 mm, Barbore 31.8 mm, Rise 25 mm, Back sweep 25°
Seatpost	Alu, 30,9 mm
Saddle	Sella Italia, Modelx SuperFlow Comfort
Tyres	Continental, Contact Cruiser, Black reflex, 55-622
Mudguards	SKS A60S
Chaincover	SKS Chainbow
Carriers	Racktime Eco2.0 - Imm system
External Lights	F: Herrmans MR GO - 120 lumen R: Axa BlueLine LED Lightguide

Motor	Bosch Active Plus 36 V, 250W
Max Torque	50 Nm
Sensor Type	Torque
Battery	PowerPack 400, weight 2,5 kg
Charger Type	2 A
Change Time	Up to 6,5 hours
Max Assisted Speed	25 km/h
Display	Purion
Power	Eco: 55 % Tour: 120 % Sport: 200 % Turbo: 300 %









-  Bosch Active Cruise
-  Powerpack 300Wh
-  Purion
-  28"
-  7s
-  26,7 kg

Black/ Anthracite	
47	0115309102

Frame	Alu, 700C, Hydroformed, Easy access, Internal PowerPack battery, Tapered, Internal routing, QR
Fork	Zoom 187D AMS, Coil, 28", Travel 65 mm, QR
Headset	Acros for Phyotn, 1,5", Internal routing
Cranckset	Miranda 38T
Rear Derailleur	LT, RD-V4007-M-2, 7s
Shifters Levers	LT, SL-V4007-7W-2, 7s
Brakes	Shimano BR-MT200, Rotor SM-RT10 180 mm/180 mm
Cassette	Shimano CS-HG200 7s 12/32
Pedals	Alu TTK
Front Hub	Shimano TX505, CL, 32h
Rear Hub	Shimano TX505, CL, HG 7, 32h
Rims	RADIALE E25, eBike Ready, Tubeless Ready, 622x25c
Stem	Alu, Barbore 31.8 mm, Adjustable
Handlebar	Alu, 640 mm, Barbore 31.8 mm, Rise 25 mm, Back sweep 25°
Seatpost	Alu, 30,9 mm
Saddle	Selle Royal Wave RVS
Tyres	Schwalbe Energizer Active Plus, Punctureguard, TwinSkin, 700x50C / Vittoria Randoneur
Mudguards	SKS A60S
Chaincover	SKS Chaincover
Carriers	Alu, without brackets
External Lights	F: Herrmans MR GO - 120 lumen R: Axa BlueLine LED Lightguide

Motor	Active 36 V, 250W
Max Torque	40 Nm
Sensor Type	Torque
Battery	Powerpack 300Wh, frametype, weight 2kg
Charger Type	2 A
Change Time	Up to 5 hours
Max Assisted Speed	25 km/h
Display	Purion
Power	Eco: 40 % Tour: 100 % Sport: 170 % Turbo: 250 %









-  Agile Gen2
-  Phylion 603Wh
-  Atala A10 LCD CAN
-  28"
-  9s
-  26,5 kg

Anthracite Matt	
45	0115311300

Frame	Alu. Hydroformed 700c, easy access, internal battery, internal cables
Fork	Suntour NVX30 NLO 700c, alu with alu crown, 63mm travel, 30mm stanchions, with hydraulic lockout
Headset	FSA integrated ahead 1 1/8
Crankset	Alu 170mm, FSA 38T
Rear Derailleur	Shimano Alivio RD-M3100
Shifters Levers	Shimano Alivio SL-M3100, 9s
Brakes	Shimano BR-MT200 hydraulic disc, Rotor 180 mm CL
Cassette	Shimano HG200 9s 11/36
Pedals	Alu Comfort
Hub	Shimano TX505, CL, 32h, quick release
Rims	Radiale E25 700c, double wall, 32h, disc
Stem	Au over, ahead, adjustable
Handlebar	Alu over TTK, 640mm, rise 25mm
Seatpost	Suspended 40mm, 30,9mm
Saddle	Selle Royal Aurorae
Tyres	Schwalbe Energizer Plus 700x55c, with reflecting line, puncture proof
Mudguards	Single stay speedy, edge
Chaincover	L type, edge
Carriers	Rear alu 14mm with spring, 25kg load
External Lights	Axa front (30 lux) and rear LED, controlled by display and twilight sensor

Motor	Agile Gen2 CAN 36 V, 250W
Max Torque	100 Nm
Sensor Type	Torque
Battery	Phylion Li-Ion 36V, 603Wh, inside frame, with Smart BMS CAN
Charger Type	2 A Europlug
Change Time	100%: 8h:52m / 80%: 6h42m
Max Assisted Speed	25 km/h
Display	Atala A10 LCD CAN, glass/metal with remote control
Power	5 levels, Power adjust level1: 50% level2: 100% level3: 150% level4: 200% level5: 250%
Other Functions	Walking assistance External light control Speed information Battery information









-  Agile Gen2
-  Phylion 522Wh
-  Atala A10 LCD CAN
-  28"
-  9s
-  26,5 kg

Green Forest	
45	0115311400
49	0115311450

Frame	Alu. Hydroformed 700c, easy access, internal battery, internal cables
Fork	Suntour NEX 700c, alu with alu crown, 63mm travel
Headset	FSA integrated ahead 1"1/8
Crankset	Alu 170mm, FSA 38T
Rear Derailleur	Shimano Acera RD-M3020
Shifters Levers	Shimano Tourney SL-RV400 RevoShift, 8s
Brakes	Shimano BR-MT200 hydraulic disc, Rotor 180 mm CL
Cassette	Shimano HG200 9s 11/36
Pedals	Alu Comfort
Hub	Shimano TX505, CL, 32h, quick release
Rims	Radiale E25 700c, double wall, 32h, disc
Stem	Au over, ahead, adjustable
Handlebar	Alu over TTK, 640mm, rise 25mm
Seatpost	Suspended 40mm, 30,9mm
Saddle	Selle Royal Aurorae
Tyres	Schwalbe Road Cruiser 700x47c, with reflecting line, puncture proof
Mudguards	Single stay speedy, edge
Chaincover	L type, edge
Carriers	Rear alu 14mm with spring, 25kg load
External Lights	Axa front (30 lux) and rear LED, controlled by display and twilight sensor

Motor	Agile Gen2 CAN 36 V, 250W
Max Torque	100 Nm
Sensor Type	Torque
Battery	Phylion Li-Ion 36V, 522Wh, inside frame, with Smart BMS CAN
Charger Type	2 A Europlug
Change Time	100%: 7h:45m / 80%: 5h48m
Max Assisted Speed	25 km/h
Display	Atala A10 LCD CAN, glass/metal with remote control
Power	5 levels, Power adjust level1: 50% level2: 100% level3: 150% level4: 200% level5: 250%
Other Functions	Walking assistance External light control Speed information Battery information









-  Agile Gen2
-  Phylion 522Wh
-  Atala A23 LCD CAN
-  28"
-  7s
-  26,7 kg

Ice White	
45	0115311500

Frame	Alu. Hydroformed 700c, easy access, internal battery, internal cables
Fork	Suntour NEX 700c, alu with alu crown, 63mm travel
Headset	FSA integrated ahead 1"1/8
Crankset	Alu 170mm, FSA 38T
Rear Derailleur	Shimano Altus RD-M310
Shifters Levers	Shimano Tourney SL-RV400 RevoShift, 7s
Brakes	Shimano BR-MT200 hydraulic disc, Rotor 160 mm CL
Cassette	Shimano HG200 7s 12/32
Pedals	Resin antislip
Hub	Shimano TX505, CL, 32h, quick release
Rims	Radiale E25 700c, double wall, 32h, disc
Stem	Au over, ahead, adjustable
Handlebar	Alu over TTK, 640mm, rise 25mm
Seatpost	Alu with clamp, 30,9mm
Saddle	Selle Royal Aurorae w/elastomer
Tyres	Byte Trento 700x45c, with reflecting line
Mudguards	Single stay speedy, edge
Chaincover	L type, edge
Carriers	Rear alu 14mm with spring, 25kg load
External Lights	Axa front (15 lux) and rear LED, controlled by display

Motor	Agile Gen2 CAN 36 V, 250W
Max Torque	100 Nm
Sensor Type	Torque
Battery	Phylion Li-Ion 36V, 522Wh, inside frame, with Smart BMS CAN
Charger Type	2 A Europlug
Change Time	100%: 7h:45m / 80%: 5h48m
Max Assisted Speed	25 km/h
Display	Atala A23 LCD CAN, side
Power	5 levels, Power adjust level1: 50% level2: 100% level3: 150% level4: 200% level5: 250%
Other Functions	Walking assistance External light control Speed information Power Information Battery information









-  Agile Gen2
-  Phylion 522Wh
-  Atala A23 LCD CAN
-  26"
-  7s
-  26,3 kg

Ultralight	
45	0115311600

Frame	Alu. Hydroformed 26", easy access, internal battery, internal cables
Fork	HL CH-187 26", alu with alu crown, 60mm travel, 30mm stanchions
Headset	FSA integrated ahead 1"1/8
Crankset	Alu 170mm, Miche 38T
Rear Derailleur	Shimano Altus RD-M310
Shifters Levers	Shimano Tourney SL-RV400 RevoShift, 7s
Brakes	Shimano BR-MT200 hydraulic disc, Rotor 160 mm CL
Cassette	Shimano HG200 7s 12/32
Pedals	Resin antislip
Hub	Shimano TX505, CL, 32h, quick release
Rims	Radiale E25 26", double wall, 32h, disc
Stem	Au over, ahead, adjustable
Handlebar	Alu over TKK, 640mm, rise 25mm
Seatpost	Alu with clamp, 30,9mm
Saddle	Selle Royal Aurorae w/elastomer
Tyres	Byte Garda 26"x2,10", with reflecting line
Mudguards	Single stay speedy, edge
Chaincover	L type, edge
Carriers	Rear alu 14mm with spring, 25kg load
External Lights	Axa front (15 lux) and rear LED, controlled by display

Motor	Agile Gen2 CAN 36 V, 250W
Max Torque	100 Nm
Sensor Type	Torque
Battery	Phylion Li-Ion 36V, 522Wh, inside frame, with Smart BMS CAN
Charger Type	2 A Europlug
Change Time	100%: 7h:45m / 80%: 5h48m
Max Assisted Speed	25 km/h
Display	Atala A23 LCD CAN, side
Power	5 levels, Power adjust level1: 50% level2: 100% level3: 150% level4: 200% level5: 250%
Other Functions	Walking assistance External light control Speed information Power Information Battery information



-  Agile CAN
-  Phylion 418Wh
-  Atala A10 LCD CAN
-  28"
-  7s
-  26,7 kg

Pastel Grey/Blue Matt







45

0115309700

Frame	Alu. Hydroformed 700c, easy access, internal battery, internal cables
Fork	Suntour NEX 700c, alu with alu crown, 50mm
Headset	FSA integrated ahead 1"1/8
Crankset	AM80 Alu 170mm, Miche 38T
Rear Derailleur	Shimano Altus RD-M310
Shifters Levers	Shimano Tourney SL-RS35 RevoShift, 7s
Brakes	Shimano BR-MT200 hydraulic disc, Rotor 160 mm CL
Cassette	Shimano HG200 7s 12/32
Pedals	Resin antislip
Hub	Shimano TX505, CL, 32h, quick release
Rims	Rodi 700c, double wall w/eylets, 32h, disc
Stem	Byte alu over, ahead, adjustable
Handlebar	Byte Alu over
Seatpost	Byte alu with clamp, 27,2mm
Saddle	Selle Royal Aurorae w/elastomer
Tyres	Byte Trento 700x45c, with reflecting line
Mudguards	Single stay speedy
Chaincover	Plastic, L type
Carriers	Rear alu 14mm with spring, 25kg load
External Lights	Axa front (15 lux) and rear LED, controlled by display and twilight sensor

Motor	AM80 Agile CAN 36 V, 250W
Max Torque	80 Nm
Sensor Type	Torque
Battery	Phylion Li-Ion 36V, 418Wh, on frame, with Smart BMS CAN
Charger Type	2 A Europlug
Change Time	100%: 6h:30m / 80%: 4h40m
Max Assisted Speed	25 km/h
Display	Atala A10 LCD CAN, glass/metal with remote control
Power	5 levels, Power adjust level1: 50% level2: 100% level3: 150% level4: 200% level5: 250%
Other Functions	Walking assistance External light control Speed information Battery information









-  AM80 Easy
-  Phylion 418Wh
-  Atala A19 Digit LED UART
-  26"
-  7s
-  23,6 kg

White Glossy	
45	0115311700

Frame	Alu. Hydroformed 26'', easy access, integrated battery, internal cables
Fork	HL CH-187 26'', alu with alu crown, 60mm travel, 30mm stanchions
Headset	FSA integrated ahead 1''1/8
Crankset	Alu 170mm, Miche 38T
Rear Derailleur	Shimano Tourney RD-TY500
Shifters Levers	Shimano Tourney SL-RS35 RevoShift, 7s
Brakes	Shimano BR-MT200 hydraulic disc, Rotor 160 mm CL
Cassette	Shimano HG200 7s 12-32
Pedals	Resin antislip
Hub	Shimano TX505, CL, 32h, quick release
Rims	Rodi 26'', double wall w/eylets, 32h, disc
Stem	Byte alu, ahead, adjustable
Handlebar	Byte steel City, 600mm, rise 60mm
Seatpost	Byte alu with clamp, 27,2mm
Saddle	Selle Royal Aurorae
Tyres	Byte Garda 26''x1,75'', with reflecting line
Mudguards	Single stay speedy, edge
Chaincover	L type, edge
Carriers	Rear steel 10mm with spring, no bracket, 25kg load
External Lights	Axa front (15 lux) and rear LED, controlled by display

Motor	AM80 Easy UART 36 V, 250W
Max Torque	70 Nm
Sensor Type	Torque
Battery	Phylion Li-Ion 36V, 418Wh, on frame, with Smart BMS UART
Charger Type	2 A Europlug
Change Time	100%: 6h:18m / 80%: 4h38m
Max Assisted Speed	25 km/h
Display	Atala A19 Digit LED UART
Power	5 levels, Power adjust level1: 50% level2: 100% level3: 150% level4: 200% level5: 250%
Other Functions	Walking assistance External light control Speed information Battery range %









-  AM80 Easy
-  Phylion 518Wh
-  Atala A19 Digit LED UART
-  26"
-  7s
-  26,6 kg

Anthracite Matt	
45	0115311800

Frame	Alu. 26'', easy access, integrated HIT, disc brake, internal cables
Fork	HL CH-187 26'', alu with alu crown, 60mm travel, 30mm stanchions
Headset	FSA integrated ahead 1''1/8
Crankset	Alu 170mm, Miche 38T
Rear Derailleur	Shimano Tourney RD-TY500
Shifters Levers	Shimano Tourney SL-RS35 RevoShift, 7s
Brakes	Shimano BR-MT200 hydraulic disc, Rotor 160 mm CL
Cassette	Shimano HG200 7s 12-32
Pedals	Resin antislip
Hub	Shimano TX505, CL, 32h, quick release
Rims	Rodi 26'', double wall w/eylets, 32h, disc
Stem	Byte alu, ahead, adjustable
Handlebar	Byte steel City, 600mm, rise 60mm
Seatpost	Byte alu with clamp, 27,2mm
Saddle	Selle Royal Wave
Tyres	Byte Garda 26''x1,75''
Mudguards	Single stay speedy, edge
Chaincover	L type, edge
Carriers	Battery rear carrier with spring, 25kg - Front carrier by tube
External Lights	Axa front (15 lux) and rear LED, controlled by display

Motor	AM80 Easy UART 36 V, 250W
Max Torque	70 Nm
Sensor Type	Torque
Battery	Phylion Li-Ion 36V, 518Wh, under carrier, with Smart BMS UART, integrated rear light
Charger Type	2 A Europlug
Change Time	100%: 7h:30m / 80%: 5h40m
Max Assisted Speed	25 km/h
Display	Atala A19 Digit LED UART
Power	5 levels, Power adjust level1: 50% level2: 100% level3: 150% level4: 200% level5: 250%
Other Functions	Walking assistance External light control Speed information Battery range %

-  Agile CAN
-  Phylion 313Wh
-  Atala A15 LED CAN
-  20"
-  7s
-  20,3 kg









Ultralight/Neon Red	
33	0115289320

Frame	Alu 20", foldable, with integrated battery
Fork	Hi-Ten Tig 20"
Headset	Integrated 1"1/8, threaded, with cap
Crankset	AM80 alu 152mm, FSA 44T
Rear Derailleur	Shimano Tourney RD-TY500
Shifters Levers	Shimano Tourney SL-RS35 RevoShift, 7s
Brakes	Shimano BR-MT200 hydraulic disc, Rotor 160 mm INT
Cassette	Shimano HG200 7s 12-32
Pedals	Resin Foldable
Hub	Shimano TX505 32h, CL, quick release
Rims	Rodi 20", double wall w/eylets, 32h, disc
Stem	Alu, foldable, adjustable
Handlebar	Alu, 30mm rise
Seatpost	Alu with clamp, 34,9mm, telescopic
Saddle	Selle Royal Lancia
Tyres	Schwalbe Big Apple 20"x2,00", with reflecting line, puncture proof
Mudguards	Single stay speedy
Chaincover	Plastic L type
Carriers	Alu rear carrier with spring
External Lights	Axa front (15 lux) and rear LED, controlled by display

Motor	AM80 Agile CAN 36 V, 250W
Max Torque	80 Nm
Sensor Type	Torque
Battery	Li-Ion 36V, 313Wh, inside down tube, with BMS
Charger Type	2 A Europlug
Charge Time	100%: 5h:20m / 80%: 3h52m
Max Assisted Speed	25 km/h
Display	Atala A15 LED CAN, Power +/-
Power	5 levels, Power adjust level1: 50% level2: 100% level3: 150% level4: 200% level5: 250%
Other Functions	Walking assistance External light control



-  Ananda
-  Li-Ion 540Wh
-  Atala A10 LCD Smart CAN
-  28"
-  8s
-  27,8 kg

Man: Black/Ultralight	
49	0115314650







Lady: Grey/Blue	
45	0115314600

Frame	Alu. 700c, integrated battery, integrated HT, disc brake, internal cables
Fork	Suntour NEX 700c, alu with alu crown, 50mm
Headset	FSA integrated 1 1/8
Crankset	Byte alu 42T cartridge
Rear Derailleur	Shimano Altus RD-M310
Shifters Levers	Shimano SL-M315 PushPull, 8s
Brakes	Hydraulic disk, Rotor 160 mm, with brake lever switch
Freewheel	DNP 8s 13-28
Pedals	Resin Antislip
Hub	Shimano quick release front, motor on rear, 36h, INT
Rims	Beretta 700c, double wall w/eylets, 36h, disc
Stem	Byte alu over, ahead, adjustable
Handlebar	Byte alu over TTK, 640mm, rise 25mm
Seatpost	Byte alu with clamp, 27,2mm
Saddle	Selle Royal Lancia
Tyres	Byte Trento 700x45c, with reflecting line
Mudguards	Single stay speedy
Chaincover	Plastic L type
Carriers	Rear alu 14mm with spring, 25kg load
External Lights	Axa front (15 lux) and rear LED, controlled by display and twilight sensor

Motor	Ananda brushless 36V 250W, on rear hub
Max Torque	45 Nm
Sensor Type	Torque
Battery	Li-Ion 36V, 540Wh, inside the frame, Samsung cells with Smart BMS CAN
Charger Type	2 A Europlug
Change Time	100%: 8h:50m / 80%: 6h40m
Max Assisted Speed	25 km/h
Display	Atala A10 LCD Smart CAN, with remote control
Power	5 levels, Speed/Torque adjust
Other Functions	Walking assistance External light control Speed information Battery information











-  Ananda
-  Li-Ion 540Wh
-  Atala A10 LCD Smart CAN
-  28"
-  8s
-  26,7 kg

Blue/Grey Matt	
45	0115314700

Frame	Alu. 700c, easy access, integrated battery, integrated HT, disc brake, internal cables
Fork	Suntour NEX 700c, alu with alu crown, 63mm
Headset	FSA integrated 1"1/8
Crankset	Byte alu 42T cartridge
Rear Derailleur	Shimano Altus RD-M310
Shifters Levers	Shimano Tourney SL-RS45 RevoShift, 8s
Brakes	Hydraulic disk, Rotor 160 mm, with brake lever switch
Freewheel	DNP 8s 13-28
Pedals	Resin Antislip
Hub	Shimano quick release front, motor on rear, 36h, INT
Rims	Beretta 700c, double wall w/eylets, 36h, disc
Stem	Byte alu over, ahead, adjustable
Handlebar	Byte alu over TTK, 640mm, rise 25mm
Seatpost	Byte alu with clamp, 27,2mm
Saddle	Selle Royal Aurorae w/elastomer
Tyres	Byte Trento 700x45c, with reflecting line
Mudguards	Single stay speedy
Chaincover	Plastic L type
Carriers	Rear alu 14mm with spring, 25kg load
External Lights	Axa front (15 lux) and rear LED, controlled by display and twilight sensor

Motor	Ananda brushless 36V 250W, on rear hub
Max Torque	45 Nm
Sensor Type	Speed sensor w/12 pulses
Battery	Li-Ion 36V, 540Wh, inside the frame, Samsung cells with Smart BMS CAN
Charger Type	2 A Europlug
Change Time	100%: 8h:50m / 80%: 6h40m
Max Assisted Speed	25 km/h
Display	Atala A10 LCD Smart CAN, with remote control
Power	5 levels, Speed/Torque adjust
Other Functions	Walking assistance External light control Speed information Battery information









-  Ananda
-  Li-Ion 540Wh
-  Atala A23 LCD CAN
-  24"
-  7s
-  25,8 kg

Anthracite	
43	0115322000

Frame	Alu. 24", easy access, integrated battery, integrated HT, disc brake, internal cables
Fork	HL CH-187 24", alu with alu crown, 60mm travel, 30mm stanchions
Headset	FSA integrated 1 1/8
Crankset	Byte alu 42T cartridge
Rear Derailleur	Shimano Altus RD-M310
Shifters Levers	Shimano Tourney SL-RV400 RevoShift, 7s
Brakes	Hydraulic disk, Rotor 180 mm, with brake lever switch
Freewheel	Shimano Tourney 7s 14-28
Pedals	Alu City
Hub	Shimano quick release front, motor on rear, 36h, INT
Rims	Rodi 24" 25c alu, double wall w/eylets, 36h
Stem	Alu over, ahead, adjustable
Handlebar	Alu over CITY 640mm, rise 60mm
Seatpost	Alu with clamp, 30,9mm
Saddle	Selle Royal Aurorae w/elastomer
Tyres	CST 24"x2,40" City
Mudguards	Steel painted
Chaincover	Steel painted, L type
Carriers	Rear alu 14mm with spring, 25kg load
External Lights	Axa front (30 lux) and rear LED, controlled by display

Motor	Ananda brushless 36V 250W, on rear hub
Max Torque	50 Nm
Sensor Type	Speed sensor w/12 pulses
Battery	Li-Ion 36V, 540Wh, inside the frame, Samsung cells with Smart BMS CAN
Charger Type	2 A Europlug
Change Time	100%: 8h:50m / 80%: 6h40m
Max Assisted Speed	25 km/h
Display	Atala A23 LCD CAN, side
Power	5 levels, Speed/Torque adjust
Other Functions	Walking assistance External light control Speed information Power information Battery information









-  Ananda
-  Phylion Li-Ion 518Wh
-  Atala A15 LED UART
-  28" / 26"
-  7s
-  27,8 kg

Lady: Black/Green	
45	0115300800

Frame	Alu. 700c, integrated battery, disc brake, internal cables /Alu. 26", easy access, integrated HT, disc brake, internal cables	Motor	Ananda brushless 36V 250W, on rear hub
Fork	HL CH-187 700c /26", alu with alu crown, 40mm	Max Torque	35 Nm
Headset	FSA integrated 1"1/8	Sensor Type	Speed sensor w/12 pulses
Crankset	Byte alu 42T cartridge	Battery	Phylion Li-Ion 36V, 518Wh, under carrier, with Smart BMS, integrated rear light
Rear Derailleur	Shimano Tourney RD-TY500	Charger Type	2 A Europlug
Shifters Levers	Shimano SL-M315 PushPull, 7s	Change Time	100%: 7h:30m / 80%: 5h40m
Brakes	Hydraulic disk, Rotor 160 mm, with brake lever switch	Max Assisted Speed	25 km/h
Freewheel	Shimano Tourney 7s 14-28	Display	Atala A15 LED UART, Power +/-
Pedals	Resin Antislip	Power	5 levels, Speed/Torque adjust
Hub	Shimano quick release front, motor on rear, 36h, INT	Other Functions	Walking assistance External light control
Rims	Beretta 700c /26", double wall w/eylets, 36h, disc		
Stem	Byte alu, adjustable		
Handlebar	Byte steel TKK		
Seatpost	Byte alu with clamp, 27,2mm		
Saddle	Selle Royal Wave		
Tyres	Byte Trento 700x45c /Byte Garda 26"x1,75"		
Mudguards	Single stay speedy		
Chaincover	Plastic L type		
Carriers	Battery rear carrier with spring, 25kg		
External Lights	Axa front (15 lux) and rear LED, controlled by display		









-  Ananda
-  Phylion Li-Ion 518Wh
-  Atala A15 LED UART
-  28"
-  7s
-  28,5 kg

Man: Black/ Neon Red	
49	0115300900

Frame	Alu. 700c, internal cables
Fork	HL CH-187 700c, alu with alu crown, 40mm
Headset	Steel 1"1/8, threaded, with cap
Crankset	Byte steel 42T cartridge, with cap
Rear Derailleur	Shimano Tourney RD-TY300
Shifters Levers	Shimano SL-M35 RevoShift, 7s
Brakes	Promax alu, V-Brake, with brake lever switch
Freewheel	Shimano Tourney 7s 14-28
Pedals	Resin City
Hub	Alu 36h, Shimano front, motor on rear
Rims	Beretta 700c, double wall w/eylets, 36h, disc
Stem	Byte alu, adjustable
Handlebar	Byte steel TKK
Seatpost	Byte alu with clamp, 27,2mm
Saddle	Selle Royal Wave
Tyres	Byte Trento 700x45c
Mudguards	Single stay speedy
Chaincover	Steel painted, L type
Carriers	Battery rear carrier with spring, 25kg
External Lights	Axa front (15 lux) and rear LED, controlled by display

Motor	Ananda brushless 36V 250W, on rear hub
Max Torque	35 Nm
Sensor Type	Speed sensor w/12 pulses
Battery	Phylion Li-Ion 36V, 518Wh, under carrier, with Smart BMS, integrated rear light
Charger Type	2 A Europlug
Change Time	100%: 7h:30m / 80%: 5h40m
Max Assisted Speed	25 km/h
Display	Atala A15 LED UART, Power +/-
Power	5 levels, Speed/Torque adjust
Other Functions	Walking assistance External light control



-  Ananda
-  Phylion Li-Ion 360Wh
-  Atala A15 LED UART
-  28" /26"
-  7s
-  28,5 kg

Man: Black/ Neon Red	
49	0115301100







Lady: Ultralight/ Anthracite	
45	0115301200

Frame	Alu. 700c, internal cables /Alu. 26", easy access, internal cables
Fork	HL CH-187 700c /26", alu with alu crown, 40mm
Headset	Steel 1"1/8, threaded, with cap
Crankset	Byte steel 42T cartridge, with cap
Rear Derailleur	Shimano Tourney RD-TY300
Shifters Levers	Shimano Tourney SL-RS35 RevoShift, 7s
Brakes	Promax alu, V-Brake, with brake lever switch
Freewheel	Shimano Tourney 7s 14-28
Pedals	Resin City
Hub	Alu 36h, Shimano front, motor on rear
Rims	Beretta 700c /26", double wall w/eylets, 36h, disc
Stem	Byte alu, adjustable
Handlebar	Byte steel TKK
Seatpost	Byte alu with clamp, 27,2mm
Saddle	Selle Royal Wave
Tyres	Byte Trento 700x45c /Byte Garda 26"x1,75"
Mudguards	Single stay speedy
Chaincover	Steel painted, L type
Carriers	Battery rear carrier with spring, 25kg
External Lights	Axa front (15 lux) and rear LED, controlled by display

Motor	Ananda brushless 36V 250W, on rear hub
Max Torque	35 Nm
Sensor Type	Speed sensor w/12 pulses
Battery	Phylion Li-Ion 36V, 360Wh, under carrier, with BMS, integrated rear light
Charger Type	2 A Europlug
Change Time	100%: 6h:4m / 80%: 4h27m
Max Assisted Speed	25 km/h
Display	Atala A15 LED UART, Power +/-
Power	5 levels, Speed/Torque adjust
Other Functions	Walking assistance External light control





-  Ananda
-  Phylion Li-Ion 518Wh
-  Atala A15 LED UART
-  28"
-  7s
-  28,4 kg

Man: Anthracite/ Neon Green	
49	0115301300

Man: White/ Red	
49	0115301500







Frame	Alu. 700c, internal cables
Fork	Hi-Ten Tig 700c
Headset	Steel 1"1/8, threaded, with cap
Crankset	Byte steel 42T cartridge, with cap
Rear Derailleur	Shimano Tourney RD-TY300
Shifters Levers	Shimano Tourney SL-RS35 RevoShift, 7s
Brakes	Promax alu, V-Brake, with brake lever switch
Freewheel	Shimano Tourney 7s 14-28
Pedals	Resin City
Hub	Alu 36h, Shimano front, motor on rear
Rims	Beretta 700c, double wall w/eylets, 36h, disc
Stem	Byte alu, adjustable
Handlebar	Byte steel TTK
Seatpost	Byte alu with clamp, 27,2mm
Saddle	Selle Royal Wave
Tyres	Byte Trento 700x45c
Mudguards	Single stay speedy
Chaincover	Steel painted, L type
Carriers	Battery rear carrier with spring, 25kg
External Lights	Axa front (15 lux) and rear LED, controlled by display

Motor	Ananda brushless 36V 250W, on rear hub
Max Torque	35 Nm
Sensor Type	Speed sensor w/12 pulses
Battery	Phylion Li-Ion 36V, 518Wh, under carrier, with Smart BMS, integrated rear light
Charger Type	2 A Europlug
Change Time	100%: 7h:30m / 80%: 5h40m
Max Assisted Speed	25 km/h
Display	Atala A15 LED UART, Power +/-
Power	5 levels, Speed/Torque adjust
Other Functions	Walking assistance External light control



Atala E-Run 7.1 28" LT








-  Ananda
-  Phylion Li-Ion 518Wh
-  Atala A15 LED UART
-  28"
-  7s
-  28,4 kg

Man LT: Anthracite/ Neon Green	
49	0115301305

Frame	Alu. 700c, internal cables
Fork	Hi-Ten Tig 700c
Headset	Steel 1"1/8, threaded, with cap
Crankset	Byte steel 42T cartridge, with cap
Rear Derailleur	L-TWOO RD-V4007-M-2, 7s
Shifters Levers	L-TWOO SL-V4007-7W-2, 7s
Brakes	Promax alu, V-Brake, with brake lever switch
Freewheel	L-TWOO FW-207 7s 13-28
Pedals	Resin City
Hub	Alu 36h, Shimano front, motor on rear
Rims	Beretta 700c, double wall w/eylets, 36h, disc
Stem	Byte alu, adjustable
Handlebar	Byte steel TTK
Seatpost	Byte alu with clamp, 27,2mm
Saddle	Selle Royal Wave
Tyres	Byte Trento 700x45c
Mudguards	Single stay speedy
Chaincover	Steel painted, L type
Carriers	Battery rear carrier with spring, 25kg
External Lights	Axa front (15 lux) and rear LED, controlled by display

Motor	Ananda brushless 36V 250W, on rear hub
Max Torque	35 Nm
Sensor Type	Speed sensor w/12 pulses
Battery	Phylion Li-Ion 36V, 518Wh, under carrier, with Smart BMS, integrated rear light
Charger Type	2 A Europlug
Change Time	100%: 7h:30m / 80%: 5h40m
Max Assisted Speed	25 km/h
Display	Atala A15 LED UART, Power +/-
Power	5 levels, Speed/Torque adjust
Other Functions	Walking assistance External light control



-  Ananda
-  Phylion Li-Ion 518Wh
-  Atala A15 LED UART
-  26"
-  7s

Ultralight/ Anthracite	
45	0115301400

White/ Blue	
45	0115301450






Frame	Alu. 26", easy access, internal cables
Fork	Hi-Ten Tig 26"
Headset	Steel 1"1/8, threaded, with cap
Crankset	Byte steel 42T cartridge, with cap
Rear Derailleur	Shimano Tourney RD-TY300
Shifters Levers	Shimano Tourney SL-RS35 RevoShift, 7s
Brakes	Promax alu, V-Brake, with brake lever switch
Freewheel	Shimano Tourney 7s 14-28
Pedals	Resin City
Hub	Alu 36h, Shimano front, motor on rear
Rims	Beretta 26", double wall w/eylets, 36h, disc
Stem	Byte alu, adjustable
Handlebar	Byte steel TTK
Seatpost	Byte alu with clamp, 27,2mm
Saddle	Selle Royal Wave
Tyres	Byte Garda 26"x1,75"
Mudguards	Single stay speedy
Chaincover	Steel painted, L type
Carriers	Battery rear carrier with spring, 25kg
External Lights	Axa front (15 lux) and rear LED, controlled by display

Motor	Ananda brushless 36V 250W, on rear hub
Max Torque	35 Nm
Sensor Type	Speed sensor w/12 pulses
Battery	Phylion Li-Ion 36V, 518Wh, under carrier, with Smart BMS, integrated rear light
Charger Type	2 A Europlug
Change Time	100%: 7h:30m / 80%: 5h40m
Max Assisted Speed	25 km/h
Display	Atala A15 LED UART, Power +/-
Power	5 levels, Speed/Torque adjust
Other Functions	Walking assistance External light control



Atala E-Run 7.1 26" LT









-  Ananda
-  Phylion Li-Ion 518Wh
-  Atala A15 LED UART
-  26"
-  7s

LT: White/ Blue	
45	0115301455

Frame	Alu. 26", easy access, internal cables
Fork	Hi-Ten Tig 26"
Headset	Steel 1"1/8, threaded, with cap
Crankset	Byte steel 42T cartridge, with cap
Rear Derailleur	L-TWOO RD-V4007-M-2, 7s
Shifters Levers	L-TWOO SL-V4007-7W-2, 7s
Brakes	Promax alu, V-Brake, with brake lever switch
Freewheel	L-TWOO FW-207 7s 13-28
Pedals	Resin City
Hub	Alu 36h, Shimano front, motor on rear
Rims	Beretta 26", double wall w/eylets, 36h, disc
Stem	Byte alu, adjustable
Handlebar	Byte steel TKK
Seatpost	Byte alu with clamp, 27,2mm
Saddle	Selle Royal Wave
Tyres	Byte Garda 26"x1,75"
Mudguards	Single stay speedy
Chaincover	Steel painted, L type
Carriers	Battery rear carrier with spring, 25kg
External Lights	Axa front (15 lux) and rear LED, controlled by display

Motor	Ananda brushless 36V 250W, on rear hub
Max Torque	35 Nm
Sensor Type	Speed sensor w/12 pulses
Battery	Phylion Li-Ion 36V, 518Wh, under carrier, with Smart BMS, integrated rear light
Charger Type	2 A Europlug
Change Time	100%: 7h:30m / 80%: 5h40m
Max Assisted Speed	25 km/h
Display	Atala A15 LED UART, Power +/-
Power	5 levels, Speed/Torque adjust
Other Functions	Walking assistance External light control



-  Ananda
-  Phylion Li-Ion 360Wh
-  Atala A15 LED UART
-  26"
-  7s
-  27,8 kg

Blue/ Champagne	
45	0115301600






White/ Red	
45	0115301650

Frame	Alu. 26", easy access, internal cables
Fork	Hi-Ten Tig 26"
Headset	Steel 1"1/8, threaded, with cap
Crankset	Byte steel 42T cartridge, with cap
Rear Derailleur	Shimano Tourney RD-TY300
Shifters Levers	Shimano Tourney SL-RS35 RevoShift, 7s
Brakes	Promax alu, V-Brake, with brake lever switch
Freewheel	Shimano Tourney 7s 14-28
Pedals	Resin City
Hub	Alu 36h, Shimano front, motor on rear
Rims	Beretta 26", double wall w/eylets, 36h, disc
Stem	Byte alu, adjustable
Handlebar	Byte steel City
Seatpost	Byte alu with clamp, 27,2mm
Saddle	Selle Royal Wave
Tyres	Byte Garda 26"x1,75"
Mudguards	Single stay speedy
Chaincover	Steel painted, L type
Carriers	Battery rear carrier with spring, 25kg / Front Carrier
External Lights	Axa front (15 lux) and rear LED, controlled by display

Motor	Ananda brushless 36V 250W, on rear hub
Max Torque	35 Nm
Sensor Type	Speed sensor w/12 pulses
Battery	Li-Ion 36V, 360Wh, under carrier, with BMS, integrated rear light
Charger Type	2 A Europlug
Charge Time	100%: 6h:4m / 80%: 4h27m
Max Assisted Speed	25 km/h
Display	Atala A15 LED UART, Power +/-
Power	5 levels, Speed/Torque adjust
Other Functions	Walking assistance External light control








-  Ananda
-  Phylion Li-Ion 360Wh
-  Atala A15 LED UART
-  26"
-  7s

LT: Blue/ Champagne	
45	0115301605

Frame	Alu. 26", easy access, internal cables
Fork	Hi-Ten Tig 26"
Headset	Steel 1"1/8, threaded, with cap
Crankset	Byte steel 42T cartridge, with cap
Rear Derailleur	L-TWOO RD-V4007-M-2, 7s
Shifters Levers	L-TWOO SL-V4007-7W-2, 7s
Brakes	Promax alu, V-Brake, with brake lever switch
Freewheel	L-TWOO FW-207 7s 13-28
Pedals	Resin City
Hub	Alu 36h, Shimano front, motor on rear
Rims	Beretta 26", double wall w/eylets, 36h, disc
Stem	Byte alu, adjustable
Handlebar	Byte steel City
Seatpost	Byte alu with clamp, 27,2mm
Saddle	Selle Royal Wave
Tyres	Byte Garda 26"x1,75"
Mudguards	Single stay speedy
Chaincover	Steel painted, L type
Carriers	Battery rear carrier with spring, 25kg / Front Carrier
External Lights	Axa front (15 lux) and rear LED, controlled by display

Motor	Ananda brushless 36V 250W, on rear hub
Max Torque	35 Nm
Sensor Type	Speed sensor w/12 pulses
Battery	Li-Ion 36V, 360Wh, under carrier, with BMS, integrated rear light
Charger Type	2 A Europlug
Change Time	100%: 6h:4m / 80%: 4h27m
Max Assisted Speed	25 km/h
Display	Atala A15 LED UART, Power +/-
Power	5 levels, Speed/Torque adjust
Other Functions	Walking assistance External light control



-  Ananda
-  Li-Ion 418Wh
-  Atala A15 LED UART
-  24"
-  7s
-  27,8 kg







Ocean	
43	0115314905

Black/Yellow	
43	0115314900

Frame	Hi-Ten Tig 24", easy access, integrated HT, internal cables
Fork	Hi-Ten Tig 24"
Headset	FSA integrated 1"1/8, ahead
Crankset	Byte steel 42T cartridge, with spider
Rear Derailleur	Shimano Tourney RD-TY300
Shifters Levers	Shimano Tourney SL-RV300 RevoShift, 7s
Brakes	Clarks CMD-23, Mechanic disk, Rotor 160mm, with brake lever switch
Freewheel	Shimano Tourney 7s 14-28
Pedals	Resin BMX
Hub	Shimano disc quick release front, motor on rear, 36h, INT
Rims	Rodi 24" 25c alu, double wall w/eylets, 36h
Stem	Alu BMX
Handlebar	Byte steel City, 680mm, rise 170mm
Seatpost	Alu, 25,4mm
Saddle	Selle Royal Wave
Tyres	CST 24"x2,40" City
Mudguards	Steel painted, no stays
Chaincover	Plastic, L type
Carriers	Rear steel 10mm, 25kg load
External Lights	Axa front (15 lux) and rear LED, controlled by display

Motor	Ananda brushless 36V 250W, on rear hub
Max Torque	50 Nm
Sensor Type	Speed sensor w/12 pulses
Battery	Li-Ion 36V, 418Wh, behind seat tube, with BMS
Charger Type	2 A Europlug
Change Time	100%: 6h:18m / 80%: 4h38m
Max Assisted Speed	25 km/h
Display	Atala A15 LED UART, Power +/-
Power	5 levels, Speed/Torque adjust
Other Functions	Walking assistance External light control



-  Ananda
-  Li-Ion 360Wh
-  Atala A15 LED UART
-  24"
-  6s
-  28 kg







White	
43	0115314505

Anthracite	
43	0115314500

Frame	Hi-Ten Tig 24", easy access, integrated HT, internal cables
Fork	Hi-Ten Tig 24"
Headset	Integrated 1"1/8, threaded, with cap
Crankset	Byte steel 42T cartridge, with cap
Rear Derailleur	Shimano Tourney RD-TZ500
Shifters Levers	Shimano Tourney SL-RS36 RevoShift, 6s
Brakes	Promax alu, Cruiser V-Brake, E-Bile pads with brake lever switch
Freewheel	Shimano Tourney 6s 14-28
Pedals	Resin city
Hub	Shimano quick release front, motor on rear, 36h, INT
Rims	Rodi 24" 25c alu, double wall w/eylets, 36h
Stem	Alu
Handlebar	Byte steel City, 600mm, rise 60mm
Seatpost	Alu, 25,4mm
Saddle	Selle Royal Wave
Tyres	CST 24"x2,40" City
Mudguards	Steel painted
Chaincover	Steel painted, L type
Carriers	Rear steel 10mm, 25kg load / front by tube
External Lights	Axa front (15 lux) and rear LED, controlled by display

Motor	Ananda brushless 36V 250W, on rear hub
Max Torque	35 Nm
Sensor Type	Speed sensor w/12 pulses
Battery	Li-Ion 36V, 360Wh, behind seat tube, with BMS
Charger Type	2 A Europlug
Charge Time	100%: 6h:4m / 80%: 4h27m
Max Assisted Speed	25 km/h
Display	Atala A15 LED UART, Power +/-
Power	5 levels, Speed/Torque adjust
Other Functions	Walking assistance External light control



-  Ananda
-  Li-Ion 360Wh
-  Atala A15 LED UART
-  26"
-  6s
-  27,6 kg

Black /Blue Light	
41	0115290600







White/ Neon Green	
41	0115290603

Frame	Hi-Ten Tig 26", easy access, internal cables
Fork	Hi-Ten Tig 26"
Headset	Steel 1"1/8, threaded, with cap
Crankset	Byte steel 42T cartridge, with cap
Rear Derailleur	Shimano Tourney RD-TZ500
Shifters Levers	Shimano Tourney SL-RS36 RevoShift, 6s
Brakes	Promax alu, V-Brake, with brake lever switch
Freewheel	Shimano Tourney 6s 14-28
Pedals	Resin City
Hub	Alu 36h, Shimano front, motor on rear
Rims	Beretta 26", double wall w/eylets, 36h, disc
Stem	Alu
Handlebar	Byte steel City
Seatpost	Alu, 25,4mm
Saddle	Selle Royal Wave
Tyres	Byte Garda 26"x1,75"
Mudguards	Single stay speedy
Chaincover	Steel painted, L type
Carriers	Rear carrier, 25kg / front carrier
External Lights	Front and rear LED, controlled by display

Motor	Ananda brushless 36V 250W, on rear hub
Max Torque	35 Nm
Sensor Type	Speed sensor w/12 pulses
Battery	Li-Ion 36V, 360Wh, behind seat tube, with BMS
Charger Type	2 A Europlug
Change Time	100%: 6h:4m / 80%: 4h27m
Max Assisted Speed	25 km/h
Display	Atala A15 LED UART, Power +/-
Power	5 levels, Speed/Torque adjust
Other Functions	Walking assistance External light control





-  Ananda
-  Li-Ion 313Wh
-  Atala A15 LED UART
-  20"
-  7s
-  23 kg

Black/ Neon Green	
33	0115302050





Frame	Alu 20", foldable, with integrated battery
Fork	Hi-Ten Tig 20"
Headset	Integrated 1"1/8, threaded, with cap
Crankset	Byte alu 152mm, 42T, cartridge
Rear Derailleur	Shimano Tourney RD-TF35
Shifters Levers	Shimano Tourney SL-RS35 RevoShift, 7s
Brakes	Promax alu, V-Brake, with brake lever switch
Freewheel	Shimano Tourney 7s 14-28
Pedals	Resin Foldable
Hub	Alu 36h, Shimano front, motor on rear
Rims	Beretta 20" alu, double wall, 36h
Stem	Alu, foldable, adjustable
Handlebar	Alu, 20mm rise
Seatpost	Alu with clamp, 34,mm, 500mm long
Saddle	Selle Royal Mach
Tyres	20"x1,75"
Mudguards	Single stay speedy
Chaincover	Plastic L type
Carriers	Alu rear carrier with spring
External Lights	Front and rear LED, controlled by display

Motor	Ananda brushless 36V 250W, on rear hub
Max Torque	35 Nm
Sensor Type	Speed sensor w/12 pulses
Battery	Li-Ion 36V, 313Wh, inside down tube, with BMS
Charger Type	2 A Europlug
Charge Time	100%: 5h:20m / 80%: 3h52m
Max Assisted Speed	25 km/h
Display	Atala A15 LED CAN, Power +/-
Power	5 levels, Speed/Torque adjust
Other Functions	Walking assistance External light control



Atala Extrafolding 7.2



-  Bafang
-  Li-Ion 630Wh
-  LCD
-  20"
-  7s
-  31,5 kg

Black/ Orange	
45	0115301755

Frame	Alu 20" FAT, foldable, integrated battery, integrated HT, disc brake, internal cables
Fork	HL CH-879 20" Fat, alu with alu crown, 32mm, with hydraulic lockout, 80mm
Headset	FSA Integrated 1"1/8
Crankset	Alu 170mm, 42T, cartridge
Rear Derailleur	Shimano Tourney RD-TF35D
Shifters Levers	Shimano Tourney SL-RS35 RevoShift, 7s
Brakes	Hydraulic disk, Rotor 180 mm, with brake lever switch
Freewheel	Shimano Tourney 7s 14-28
Pedals	Resin Foldable
Hub	Alu 36h, axle 135 F/175 R, motor on rear
Rims	20" alu, double wall, 36h
Stem	Alu, foldable, adjustable
Handlebar	Alu, 20mm rise
Seatpost	Alu with clamp, 33,9,mm
Saddle	Selle Royal Wave
Tyres	20"x4
Mudguards	Steel painted
Chaincover	Paracatena
Carriers	Alu rear carrier custom, 25kg
External Lights	Axa front (30Lux) and rear LED, controlled by display

Motor	Bafang brushless 36V 250W, on rear hub
Sensor Type	Speed sensor w/12 pulses
Battery	Li-Ion 36V, 630Wh, inside the frame, Samsung cells with BMS
Charger Type	2 A Europlug
Charge Time	100%: 10h:14m / 80%: 7h47m
Max Assisted Speed	25 km/h
Display	LCD, Power +/-
Power	5 levels, Speed/Torque adjust
Other Functions	Walking assistance External light control Speed information

Atala Extrafolding 7.1



-  Bafang
-  Li-Ion 630Wh
-  LCD
-  20"
-  7s
-  31,5 kg

Black/ Orange	
45	0115314750

Black/ Anthracite	
45	0115314700


Frame	Alu 20" FAT, foldable, integrated battery, integrated HT, disc brake, internal cables
Fork	Susp 45mm 20"x4", alu crown, with mechanical lockout
Headset	FSA Integrated 1"1/8
Crankset	Alu 170mm, 42T, cartridge
Rear Derailleur	Shimano Tourney RD-TF35D
Shifters Levers	Shimano Tourney SL-RS35 RevoShift, 7s
Brakes	Hydraulic disk, Rotor 180 mm, with brake lever switch
Freewheel	Shimano Tourney 7s 14-28
Pedals	Resin Foldable
Hub	Alu 36h, axle 135 F/175 R, motor on rear
Rims	20" alu, double wall, 36h
Stem	Alu, foldable, adjustable
Handlebar	Alu, 20mm rise
Seatpost	Alu with clamp, 33,9,mm
Saddle	Selle Royal Wave
Tyres	20"x4
Mudguards	Steel painted
Chaincover	Paracatena
Carriers	Alu rear carrier custom, 25kg
External Lights	Axa front (30Lux) and rear LED, controlled by display

Motor	Bafang brushless 36V 250W, on rear hub
Sensor Type	Speed sensor w/12 pulses
Battery	Li-Ion 36V, 630Wh, inside the frame, Samsung cells with BMS
Charger Type	2 A Europlug
Charge Time	100%: 10h:14m / 80%: 7h47m
Max Assisted Speed	25 km/h
Display	LCD, Power +/-
Power	5 levels, Speed/Torque adjust
Other Functions	Walking assistance External light control Speed information



Atala Extrafolding 7.1 E



-  Bafang
-  Li-Ion 522Wh
-  LCD
-  20"
-  7s
-  31,5 kg

Black/ Orange	
45	0115314800




Black/ Anthracite	
45	0115314850

Frame	Alu 20" FAT, foldable, integrated battery, integrated HT, disc brake, internal cables
Fork	Susp 45mm 20"x4", alu crown, with mechanical lockout
Headset	FSA Integrated 1"1/8
Crankset	Alu 170mm, 42T, cartridge
Rear Derailleur	Shimano Tourney RD-TF35D
Shifters Levers	Shimano Tourney SL-RS35 RevoShift, 7s
Brakes	Hydraulic disk, Rotor 180 mm, with brake lever switch
Freewheel	Shimano Tourney 7s 14-28
Pedals	Resin Foldable
Hub	Alu 36h, axle 135 F/175 R, motor on rear
Rims	20" alu, double wall, 36h
Stem	Alu, foldable, adjustable
Handlebar	Alu, 20mm rise
Seatpost	Alu with clamp, 33,9,mm
Saddle	Selle Royal Wave
Tyres	20"x4
Mudguards	Steel painted
Chaincover	Paracatena
Carriers	Alu rear carrier custom, 25kg
External Lights	Axa front (30Lux) and rear LED, controlled by display

Motor	Bafang brushless 36V 250W, on rear hub
Sensor Type	Speed sensor w/12 pulses
Battery	Li-Ion 36V, 522Wh, inside the frame, with BMS
Charger Type	2 A Europlug
Charge Time	100%: 8h:33m / 80%: 6h27m
Max Assisted Speed	25 km/h
Display	LCD, Power +/-
Power	5 levels, Speed/Torque adjust
Other Functions	Walking assistance External light control Speed information





-  Bafang
-  Li-Ion 540Wh
-  LCD
-  20"
-  7s
-  31 kg

Black/ Yellow	
43	0115312700

Neon Green/ Black	
43	0115290705

Frame	Alu 20" FAT, foldable, integrated HT, disc brake
Fork	Susp 45mm 20"x4", alu crown, with mechanical lockout
Headset	Integrated 1"1/8, threaded
Crankset	Alu 170mm, 42T, cartridge
Rear Derailleur	Shimano Tourney RD-TF35D
Shifters Levers	Shimano Tourney SL-RS35 RevoShift, 7s
Brakes	Hydraulic disk, Rotor 180 mm, with brake lever switch
Freewheel	Shimano Tourney 7s 14-28
Pedals	Resin Foldable
Hub	Alu 36h, axle 135 F/175 R, motor on rear
Rims	20" alu, double wall, 36h
Stem	Alu, foldable, adjustable
Handlebar	Alu, 20mm rise
Seatpost	Alu with clamp, 27,2mm, 400mm long
Saddle	Selle Royal Wave
Tyres	20"x4
Mudguards	Steel painted
Chaincover	Paracatena
Carriers	Alu integrato al telaio
External Lights	Spanninga front (16Lux) and rear LED, controlled by display

Motor	Bafang brushless 36V 250W, on rear hub
Sensor Type	Speed sensor w/12 pulses
Battery	Li-Ion 36V, 540Wh, behind seat tube, with BMS
Charger Type	2 A Europlug
Charge Time	100%: 8h:50m / 80%: 6h40m
Max Assisted Speed	25 km/h
Display	LCD, Power +/-
Power	5 levels, Speed/Torque adjust
Other Functions	Walking assistance External light control Speed information



E-BIKE 2024



WHISTLE

Atala

L'azienda si riserva il diritto di modificare le immagini ed i componenti in ogni momento e senza alcun preavviso.

The company reserves the right to modify pictures and the bicycle parts at anytime without prior notice.